

## Sleeve frame - VC-TR1/2M-PEA - 1607059

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve frame, with PE connection to housing, for contact insert modules, type 1, number of insert modules: 2

The illustration shows the version  
VC-TR 1/2 M-PEA

### Product Features

- Compact design
- Universal connection
- Proven COMBICON technology
- Can be keyed to prevent incorrect connection



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	15.95 g
Custom tariff number	85389099
Country of origin	Poland

### Technical data

#### Dimensions

Height	27.5 mm
Width	50.2 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
---------------------------------	-------------------

#### General

Size	VC1
Color	black

# Sleeve frame - VC-TR1/2M-PEA - 1607059

## Technical data

### General

Material	PA
Housing material	Plastic
Flammability rating according to UL 94	V0

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27189239
eCl@ss 5.1	27189239
eCl@ss 6.0	27144001
eCl@ss 7.0	27144001
eCl@ss 8.0	27440210
eCl@ss 9.0	27440210

### ETIM

ETIM 2.0	EC000007
ETIM 3.0	EC000007
ETIM 4.0	EC000007
ETIM 5.0	EC002310

### UNSPSC

UNSPSC 6.01	43172601
UNSPSC 7.0901	31261501
UNSPSC 11	43172601
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Approvals

### Approvals

---

Approvals

EAC

# Sleeve frame - VC-TR1/2M-PEA - 1607059

## Approvals

Ex Approvals


Approvals submitted

## Approval details

EAC

## Drawings

Functional drawing



Dimensional drawing

