

5


4

3

2

1

Edge mark on first conductor



Wire _____ Tinned copper

Gauge _____ AWG 28/7 0,089 mm²

Voltage rating _____ 300 Vr.m.s

Current rating _____ 2,1A at 25°C

Capacity unbalanced _____ 45,9 pF/m at 1 MHz

Impedance unbalanced _____ 105 Ω

Propagation delay _____ 4,9 ns/m nominal


Insulation material _____ PVC

Temperature rating _____ -20°C (operating)
 _____ -30°C (static) to +105°C

Flammability rating _____ Flame retardant VW1

Insulation resistance _____ 100 MΩ/km

Approval _____ UL AWM style 2651

				Dat.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 flat cable 40 poles	Maßstab/ Scale 10:1
			Detail.	20/10/05	JMDR			
			Insp.					
			Stand.					
EC01360	19/02/10	SC						
34400	18/09/07	PK						
33246	20/10/05	JMDR						
Mod.	Dat.	Name						

09 18 040 7004	100 m (328 feet)
09 18 040 7001	30,48 m (100 feet)
Part number	Length per reel

HARTING EURL
F-95972 Paris



TB 09 18 040 700X	Blatt/ Page 1/1
Sub.	