

## Photovoltaic connector - PV-FT-CF-C-4-200-BU-SP - 1705086

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RoHS

### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 50 pc                                                                                                   |
| Minimum order quantity | 50 pc                                                                                                   |
| GTIN                   | <br>4 046356 752244 |
| GTIN                   | 4046356752244                                                                                           |


### Technical data

#### Environmental Product Compliance


|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings

Dimensional drawing



Dimensional drawing



Dimension x = cable length  
c: panel thickness - plastic: 2 - 6 mm; metal: 2 - 5 mm

## Photovoltaic connector - PV-FT-CF-C-4-200-BU-SP - 1705086

### Approvals

#### Approvals

---

#### Approvals

TÜV Rheinland / VDE Zeichengenehmigung / EAC

---

#### Ex Approvals

---

#### Approval details

|                    |                                                                   |            |
|--------------------|-------------------------------------------------------------------|------------|
| TÜV Rheinland      | <a href="http://www.certipedia.com">http://www.certipedia.com</a> | R 60126961 |
|                    |                                                                   |            |
| Nominal voltage UN | 1500 V                                                            |            |

|                        |                                                                                    |                                                                                                                                                                                                           |          |
|------------------------|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Zeichengenehmigung |  | <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> | 40031807 |
|                        |                                                                                    |                                                                                                                                                                                                           |          |
| Nominal voltage UN     | 1500 V                                                                             |                                                                                                                                                                                                           |          |
| Nominal current IN     | 40 A                                                                               |                                                                                                                                                                                                           |          |
| mm²/AWG/kcmil          | 4                                                                                  |                                                                                                                                                                                                           |          |

|     |                                                                                     |         |
|-----|-------------------------------------------------------------------------------------|---------|
| EAC |  | B.00767 |
|-----|-------------------------------------------------------------------------------------|---------|

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>