


## Pan-Ty® Cable Ties – Metal Detectable Nylon 6.6 and Polypropylene

- Metal impregnated material allows identification by metal detectors or x-ray inspection equipment to help meet food, beverage, and pharmaceutical safety standards, to help reduce product contamination, loss, and recall
- Nylon material for general purpose maintenance and repair applications; ideal for use in control panels and overhead cable runs
- Polypropylene material provides excellent chemical resistance for use in processing and packaging areas where aggressive acid and alkaline chemicals are used to clean the equipment
- One-piece construction for consistent performance and reliability
- Lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



| Part Number   | Length |     | Width |     | Thickness |     | Max. Bundle Dia. |     | Min. Loop Tensile Strength |     | Recommended Installation Tool          | Material      | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---|--------|-----|-------|-----|-----------|-----|------------------|-----|----------------------------|-----|--|---------------|----------------|----------------|
|   | In.    | mm  | In.   | mm  | In.       | mm  | In.              | mm  | Lbs.                       | N   |  |               |                |                |
| <b>Nylon 6.6</b>  |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| <b>Miniature Cross Section</b>  |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT1M-C86   | 3.9    | 100 | .098  | 2.5 | .044      | 1.1 | .87              | 22  | 18                         | 80  | GTS, GTSL, GS2B, STS2                  | Nylon 6.6     | 100            | 1000           |
| <b>Intermediate Cross Section</b>   |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT2I-C86   | 8.0    | 203 | .135  | 3.4 | .047      | 1.2 | 2.00             | 51  | 40                         | 178 | GTS, GTSL, GS2B, STS2                  | Nylon 6.6     | 100            | 1000           |
| <b>Standard Cross Section</b>   |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT2S-C86   | 7.3    | 186 | .190  | 4.8 | .057      | 1.4 | 1.85             | 47  | 50                         | 222 | GTS, GTSL, GS2B, GTH, GS4H, STS2, STH2 | Nylon 6.6     | 100            | 1000           |
| PLT3S-C86   | 11.5   | 291 | .190  | 4.8 | .057      | 1.4 | 3.00             | 76  | 50                         | 222 |  | Nylon 6.6     | 100            | 1000           |
| PLT4S-C86   | 14.4   | 366 | .190  | 4.8 | .057      | 1.4 | 4.00             | 102 | 50                         | 222 |  | Nylon 6.6     | 100            | 1000           |
| <b>Light-Heavy Cross Section (Straight Tip)</b>   |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT3H-L86   | 11.1   | 282 | .300  | 7.6 | .075      | 1.9 | 3.00             | 76  | 120                        | 120 | GTH, GS4H, GS4EH, STH2, ST3EH          | Nylon 6.6     | 50             | 500            |
| PLT4H-L86   | 14.4   | 366 | .300  | 7.6 | .075      | 1.9 | 4.00             | 102 | 120                        | 120 |  | Nylon 6.6     | 50             | 500            |
| <b>Polypropylene</b>  |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| <b>Miniature Cross Section</b> <span style="color: red; font-weight: bold;">NEW!</span> |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT1M-C186  | 3.9    | 100 | 0.098 | 2.5 | 0.044     | 1.1 | 0.87             | 22  | 15                         | 67  | GTS, GTSL, GS2B, STS2                  | Polypropylene | 100            | 1000           |
| <b>Intermediate Cross Section</b>   |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT2I-C186  | 8.0    | 203 | .135  | 3.4 | .047      | 1.2 | 2.00             | 51  | 24                         | 107 | GTS, GTSL, GS2B, STS2                  | Polypropylene | 100            | 1000           |
| <b>Standard Cross Section</b>   |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT2S-C186  | 7.3    | 186 | .190  | 4.8 | .057      | 1.4 | 1.85             | 47  | 30                         | 133 | GTS, GTSL, GS2B, GTH, GS4H, STS2, STH2 | Polypropylene | 100            | 1000           |
| PLT3S-C186  | 11.5   | 291 | .190  | 4.8 | .057      | 1.4 | 3.00             | 76  | 30                         | 133 |  | Polypropylene | 100            | 1000           |
| PLT4S-C186  | 14.4   | 366 | .190  | 4.8 | .057      | 1.4 | 4.00             | 102 | 30                         | 133 |  | Polypropylene | 100            | 1000           |
| <b>Light-Heavy Cross Section (Straight Tip)</b>   |        |     |       |     |           |     |                  |     |                            |     |  |               |                |                |
| PLT3H-L186  | 11.1   | 282 | .300  | 7.6 | .075      | 1.9 | 3.00             | 76  | 60                         | 267 | GTH, GS4H, GS4EH, STH2, ST3EH          | Polypropylene | 50             | 500            |
| PLT4H-L186  | 14.4   | 366 | .300  | 7.6 | .075      | 1.9 | 4.00             | 102 | 60                         | 267 |  | Polypropylene | 50             | 500            |

| Part Number  | Material      | Used with Cable Ties | A Length In. (mm) | B Width In. (mm) | C Height In. (mm) | Counterbore Diameter In. (mm) | Mounting Method | Std. Pkg. Qty. | Std. Ctn. Qty. |
|--|---------------|----------------------|-------------------|------------------|-------------------|-------------------------------|-----------------|----------------|----------------|
| <b>Cable Tie Mounts</b> <span style="color: red; font-weight: bold;">NEW!</span> |               |                      |                   |                  |                   |                               |                 |                |                |
| TM2S8-C86  | Nylon 6.6     | Min., Int., Std.     | .630 (16.0)       | .422 (10.7)      | .275 (7.0)        | .325 (8.3)                    | #8 (M4) screw   | 100            | 500            |
| TM3S8-C86  |               | Std., Lt. Hvy.       | .867 (22.0)       | .614 (15.6)      | .373 (9.5)        | .325 (8.3)                    | #8 (M4) screw   | 100            | 500            |
| TM3S10-C86   |               |                      |                   |                  |                   |                               | #10 (M5) screw  | 100            | 500            |
| TM2S8-C186   | Polypropylene | Min., Int., Std.     | .630 (16.0)       | .422 (10.7)      | .275 (7.0)        | .325 (8.3)                    | #8 (M4) screw   | 100            | 500            |
| TM3S8-C186   |               | Std., Lt. Hvy.       | .867 (22.0)       | .614 (15.6)      | .373 (9.5)        | .325 (8.3)                    | #8 (M4) screw   | 100            | 500            |
| TM3S10-C186  |               |                      |                   |                  |                   |                               | #10 (M5) screw  | 100            | 500            |

