






THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION



Pin Assignment
Front View



Recommended
Panel Cut-Out

Note:
* $\varnothing$ Important Dimension.
* Waterproof Rate: IP67.
* Housing: Nylon+GF, Black.
* Male Pin: Copper Alloy, Gold Plated.
* Screw Nut: Nylon+GF, Black.
* O-Ring: EPDM, Black.
* For Panel Thickness Max 3.0mm.

UNIT:mm		TITLE M8 4Pin Panel M Conn. M Pin		ITEM NO 8AP-04PMMS-SF7001		DRAWN BY Mila		DATE 2013-12-19	
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 3:1	SIZE A4	SHEET 1 OF 1	DWG NO 8AP-04PMMS-SF7001	CHECKED BY Jimmy		DATE 2013-12-19	
REV. A		WC-REV. A.4	$\varnothing$: Inspection item		CUSTOMER ALTW	APPROVED BY Jerry		DATE 2013-12-19	

Amphenol LTW
安費諾亮泰企業股份有限公司