# 9001SKP7R31



## Main

Product or component type	Pilot light
Lens type	Fresnel plastic
Light block supply	Via transformer (f = 50/60 Hz) Via integral transformer (f = 50/60 Hz)

## Complementary

-		
Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
Cap/operator or lens colour	Red	
Light source	Incandescent	
Bulb base	BA 9s	
[Us] rated supply voltage	220240 V AC	
Operating position	Any position	
Operating mode	Normal	
CAD overall width	2.13 in (54 mm)	-
CAD overall height	2.76 in (70 mm)	
CAD overall depth	1.65 in (42 mm)	
Device presentation	Complete product	

#### **Environment**

protective treatment	TC	E G
IP degree of protection	IP66	

## Offer Sustainability

785901041719	785901041719
Compliant - since 0921 - Schneider Electric declaration of conformity	Compliant - since 0921 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

## Contractual warranty

Warranty period	18 months	