




CROSS SECTION THRU FLAT

Part Number	Count	Pairs	A Span	B Span
125-3096-996	68	34	1.701 ±0.012	1.675 ±0.010

Alternative Twist Lengths Available, Consult Factory for Ordering Information.

All Dimensions in Inches, Unless Otherwise Noted

PHYSICAL

Conductors: 30 AWG Solid Tinned Copper
 Insulation: .007" TPE
 Color Code: 1st Pair Blue/White followed by Orange/White and Repeat
 Laminate: Polyester
 Temperature Rating: 80°C

ELECTRICAL

Impedance: 93 ohms¹
 131 ohms²
 Capacitance: 15.3 pF/ft @ 1 MHz
 11.4 pF/ft @ 1 MHz²
 Propagation Delay: 1.45 ns/ft
 Voltage Rating: 150 V
 Current Rating: 0.75 A
 DC Resistance: 105 ohm per 1,000 ft @ 20°C

¹ Above values measured Single-Ended, with one conductor of each pair commoned to one Bus(SCSI Mode)

² Above values measured Differentially.

Approvals: UL AWM Style 20744
 CSA AWM

Print Legend: **Amphenol SPECTRA-STRIP**

⌘[®]AWM 80C LL31941 CSA AWM I A80C 150V FT-1
 <Date Code> Spectra-Green Lead Free/PBB Free

DRAWN	PROD ENG	QA	MKT	P/ECN#	DRAWING NO.	AMPHENOL SPECTRA-STRIP 720 SHERMAN AVE TEL (203) 281-3200 HAMDEN CT 06514 FAX (203) 281-5872	Rev D
FITS 5/20/98	8/4/04			780	TITLE: .025" Twist 'N' Flat		SHEET 1 of 1
					Full Lamination, 30 AWG Solid		