

## 5500UG Multi-Conductor - Residential, Light Commercial and Institutional Applications



For more Information  
please call

1-800-Belden1



### General Description:

Security & Alarm Cable, Rated-CM, 2-22 AWG stranded bare copper conductors with polyolefin insulation, PVC jacket

### Physical Characteristics (Overall)

#### Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 2            | 22  | 7x30      | BC - Bare Copper   |

Total Number of Conductors: 2

#### Insulation

Insulation Material:

| Insulation Material | Wall Thickness (in.) |
|---------------------|----------------------|
| PP - Polypropylene  | .006                 |

#### Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

#### Outer Jacket

Outer Jacket Material:

| Outer Jacket Material    | Nom. Wall Thickness (in.) |
|--------------------------|---------------------------|
| PVC - Polyvinyl Chloride | .015                      |

#### Overall Cable

Overall Cabling Color Code Chart:

| Color |
|-------|
| Black |
| Red   |

Overall Nominal Diameter: 0.114 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 7.300 lbs/1000 ft.

Max. Recommended Pulling Tension: 18.200 lbs.

Min. Bend Radius/Minor Axis: 1.200 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CM

NEC Articles: 800

CEC/C(UL) Specification: CM

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

## 5500UG Multi-Conductor - Residential, Light Commercial and Institutional Applications

CA Prop 65 (CJ for Wire & Cable): Yes

Mil Order #39 (China RoHS): Yes

### Flame Test

UL Flame Test: UL1685 UL Loading

CSA Flame Test: FT1

### Plenum/Non-Plenum

Plenum (Y/N): No

### Electrical Characteristics (Overall)

#### Nom. Inductance:

Inductance (µH/ft)

.155

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

20

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

16.1

#### Max. Operating Voltage - UL:

Voltage

300 V RMS

#### Max. Recommended Current:

Current

2.8 Amps per conductor @ 25°C

### Put Ups and Colors:

| Item #          | Putup    | Ship Weight | Color       | Notes | Item Desc      |
|-----------------|----------|-------------|-------------|-------|----------------|
| 5500UG U4FC1000 | 1,000 FT | 7.000 LB    | BEIGE U4F   |       | 2 #22 PP FRPVC |
| 5500UG U4FU500  | 500 FT   | 4.500 LB    | BEIGE U4F   |       | 2 #22 PP FRPVC |
| 5500UG 001C1000 | 1,000 FT | 7.000 LB    | BROWN       |       | 2 #22 PP FRPVC |
| 5500UG 001C500  | 500 FT   | 3.500 LB    | BROWN       |       | 2 #22 PP FRPVC |
| 5500UG 003C500  | 500 FT   | 3.500 LB    | ORANGE      |       | 2 #22 PP FRPVC |
| 5500UG 003U500  | 500 FT   | 4.500 LB    | ORANGE      |       | 2 #22 PP FRPVC |
| 5500UG 004C1000 | 1,000 FT | 7.000 LB    | YELLOW      |       | 2 #22 PP FRPVC |
| 5500UG 004C500  | 500 FT   | 3.500 LB    | YELLOW      |       | 2 #22 PP FRPVC |
| 5500UG 004U500  | 500 FT   | 4.500 LB    | YELLOW      |       | 2 #22 PP FRPVC |
| 5500UG 005C1000 | 1,000 FT | 7.000 LB    | GREEN, DARK |       | 2 #22 PP FRPVC |
| 5500UG 005C500  | 500 FT   | 3.500 LB    | GREEN, DARK |       | 2 #22 PP FRPVC |
| 5500UG 005U500  | 500 FT   | 4.500 LB    | GREEN, DARK |       | 2 #22 PP FRPVC |
| 5500UG 006U500  | 500 FT   | 4.500 LB    | BLUE, LIGHT |       | 2 #22 PP FRPVC |
| 5500UG 007C1000 | 1,000 FT | 7.000 LB    | VIOLET      |       | 2 #22 PP FRPVC |
| 5500UG 007C500  | 500 FT   | 3.500 LB    | VIOLET      |       | 2 #22 PP FRPVC |
| 5500UG 007U500  | 500 FT   | 4.500 LB    | VIOLET      |       | 2 #22 PP FRPVC |
| 5500UG 008C1000 | 1,000 FT | 7.000 LB    | GRAY        |       | 2 #22 PP FRPVC |
| 5500UG 008C500  | 500 FT   | 3.500 LB    | GRAY        |       | 2 #22 PP FRPVC |
| 5500UG 008U1000 | 1,000 FT | 8.000 LB    | GRAY        |       | 2 #22 PP FRPVC |
| 5500UG 009C1000 | 1,000 FT | 7.000 LB    | WHITE       |       | 2 #22 PP FRPVC |
| 5500UG 009C500  | 500 FT   | 3.500 LB    | WHITE       |       | 2 #22 PP FRPVC |
| 5500UG 009U1000 | 1,000 FT | 8.000 LB    | WHITE       |       | 2 #22 PP FRPVC |

Revision Number: 1 Revision Date: 03-11-2013

© 2014 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.