





230 MAX. 200 175 125 75 50 25	REFLOW PROFILE  B SEC. MAX.  90-120 SEC.
0	90 180
	TIME (SECONDS)

PARAMETER         MIN         TYP         MAX         UNITS         TEST COND           PEAK WAVELENGTH         660         nm           FORWARD VOLTAGE         1.7         2.2         V <sub>f</sub> REVERSE VOLTAGE         4.0         V <sub>r</sub> I <sub>r</sub> =100μA           AXIAL INTENSITY         300         mcd         I <sub>f</sub> = 20mA           VIEWING ANGLE         50         2x theta           EMITTED COLOR:         RED           EPOXY LENS FINISH:         WATER CLEAR	ELECTRO-OPTICAL CH	ARACTER	ISTICS TA=25°C		l f=20mA	
FORWARD VOLTAGE 1.7 2.2 $V_f$ REVERSE VOLTAGE 4.0 $V_r$ $I_r = 100 \mu A$ AXIAL INTENSITY 300 mcd $I_f = 20 mA$ VIEWING ANGLE 50 $2x$ theta EMITTED COLOR: RED	PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
REVERSE VOLTAGE 4.0 $V_r$ $I_r = 100 \mu A$ AXIAL INTENSITY 300 mcd $I_f = 20 mA$ VIEWING ANGLE 50 2x theta EMITTED COLOR: RED	PEAK WAVELENGTH		660		nm	
AXIAL INTENSITY 300 mcd $l_f = 20$ mA VIEWING ANGLE 50 2x theta EMITTED COLOR: RED	FORWARD VOLTAGE		1.7	2.2	$v_f$	
VIEWING ANGLE 50 2x theta EMITTED COLOR: RED	REVERSE VOLTAGE	4.0			٧r	I <sub>r</sub> =100μΑ
EMITTED COLOR: RED	AXIAL INTENSITY		300		mcd	$I_f = 20 \text{mA}$
	VIEWING ANGLE		50		2x theta	
EPOXY LENS FINISH: WATER CLEAR	EMITTED COLOR:	RED				
	EPOXY LENS FINISH:	WATER	CLEAR			

PART NUMBER

SML-LXL1307SRC-TR

E.C.N. NUMBER AND REVISION COMMENTS

### LIMITS OF SAFE OPERATION AT 25°C

E.C.N. #10909.

REV.

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	—1.6	mW∕°C
OPERATING, STORAGE TEMP.	- 40 TO + 85	<b>'</b> C
* t<10us		

## NOTES:

△ 1. 2,000 PIECES PER REEL.

2. THE POLARITY MARK IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

#### CAUTION: MOISTURE SENSITIVE DEVICE

- . SHELF LIFE IN SEALED BAG:
- 12 MONTHS AT <40°C AND <90% RELATIVE HUMIDITY (RH). AFTER THIS BAG IS OPENED, DEVICES HAVE TO BE
- NOUNTED WITHIN 48 HOURS OR STORED AT <30% RH.

# TOP TAPE TAPE FEED DIRECTION ---

8.00 [0.315]

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005), LEAD SIZE=±0.05 (0.002), LEAD LENGTH=±0.75 (±0.000), MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.000), MIN= +DECIMAL PRECISION MAX.= +0.00 (±0.000), X.XX=±0.127 (±0.000

2.00 [0.079]

REV. PART NUMBER SML-LXL1307SRC-TR

> 3.2mm x 1.6mm PCB SURFACE MOUNT LED. 660nm SUPER RED LED, WATER CLEAR DOME LENS, TAPE AND REEL.

2.00 [0.079]

ø1.55 [ø0.061]

1.75 [0.069]

3.50 [0.138]

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE GR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RECOMMENDED SOLDER PAD LAYOUT

1.50 [0.059]

1.75 [0.069]

(2 PLS.)

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359,2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY:

APPROVED BY:

DATE: 1.12.01 1 OF 1 PAGE: SCALE: N/A

REV.

DATE 9.17,02