

JACKET DIA. .088 MAX.
DIELECTRIC DIA. .038 MAX.
CENTER COND. DIA. .015 MAX.



1. THIS CONNECTOR MATES WITH ALL S-50 JACKS AND RECEPTACLES AS LISTED IN MALCO CATALOG.

2. FOR ASSEMBLY INSTRUCTIONS SEE RF-ASMB-89

3. MALCO ASSEMBLY TOOL #T-3221 OR 010-0003-0000.

4. OPTIONAL: DEPENDING ON CUSTOMER REQUIREMENTS.

5. SILVER PLATE: 0002-0004 PER 00-S-365.

6. GOLD PLATE. 00005 MIN. PER MIL-G-45204, TYPE II, CL. I.

7. 10-32 UNF-2B THD

REVISIONS

FINISH	QTY.	ASTERISK NO.	PT. NO.	DESCRIPTION	MAT'L & SPEC.	ITEM NO.
	7	1	003-0270-0000	BEND RELIEF CAP	SILICONE RUBBER ZZ-B-1065	2
	1	1	003-0153-0001	BUSHING	TEFLON L-P-403	8
	1	1	003-0597-0001	FERRULE PIN PROTECTOR	TEFLON L-P-403	7
5	1	1	003-0163-0001	RING	BRASS QQ-B-626	6
5	1	1	005-0355-0001	FERRULE	BRASS QQ-B-626	5
	1	1	003-0205-0001	BUSHING	TEFLON L-P-403	4
5	1	1	003-0360-0002	PIN	BRASS QQ-B-626	3
5	1	1	003-0772-0001	1" HEX NUT - WITH SAFETY WIRE HOLES	BRASS QQ-B-626	2
5	1	1	003-0454-0001	1/4" HEX NUT	BRASS QQ-B-626	1
	3	2				

PARTS LIST

3

2

TYCO CUSTOMER DRAWING
5-1532146-1