



ENK Series

AHS-V (Form A)



AV




Switching Operation

1 NC / 1 NO Contacts


Slow Action

608.1135.003
ENK-U1Z AHS-V




Snap Action

608.1185.009
ENK-SU1Z AHS-V




Slow Action

608.1136.012
ENK-U1 AV




Snap Action

608.1186.018
ENK-SU1 AV



2 NC Contacts

608.1835.323
ENK-A2Z AHS-V



-

-

2 NO Contacts

-


-

-

-

1 NC / 1 NO Contacts Overlapping

608.1335.006
ENK-UV1Z AHS-V



-

-

Replacement actuator:

391.8350.737

391.8360.738

Technical Information

Slow Action

Snap Action

Maximum Switching Voltage	240V
Max. Switching Amps (up to)*	10A
B10d (up to)*	20 Million
Mechanical Service Life (up to)*	3 x 10 ⁶
Switching Frequency	≤ 100/min
Operating Temperature	-30 °C to +80 °C
Protection Rating	IP65
Utilization Category (up to)*	AC-15, Ue/Ue 240V 3A
Rate Insulation Voltage	400VAC

Maximum Switching Voltage	240V
Max. Switching Amps (up to)*	10A
B10d (up to)*	20 Million
Mechanical Service Life (up to)*	10 x 10 ⁶
Switching Frequency	≤ 100/min
Operating Temperature	-30 °C to +80 °C
Protection Rating	IP65
Utilization Category (up to)*	AC-15, Ue/Ue 240V 3A
Rate Insulation Voltage	400VAC

Slow Action

Snap Action

Maximum Switching Voltage	240V
Max. Switching Amps (up to)*	10A
B10d (up to)*	20 Million
Mechanical Service Life (up to)*	10 x 10 ⁶
Switching Frequency	≤ 100/min
Operating Temperature	-30 °C to +80 °C
Protection Rating	IP65
Utilization Category (up to)*	AC-15, Ue/Ue 240V 3A
Rate Insulation Voltage	400VAC

Maximum Switching Voltage	240V
Max. Switching Amps (up to)*	10A
B10d (up to)*	20 Million
Mechanical Service Life (up to)*	10 x 10 ⁶
Switching Frequency	≤ 100/min
Operating Temperature	-30 °C to +80 °C
Protection Rating	IP65
Utilization Category (up to)*	AC-15, Ue/Ue 240V 3A
Rate Insulation Voltage	400VAC

Approvals

* Depending on switching system - see technical information for details



Special features/variants (on request)

- Available with black enclosure
- With 50 mm diameter rubber roller
- 3 NC contacts possible

Special features/variants (on request)

- Available with different lever lengths
- With 50 mm diameter rubber roller

Drawing dimensions in mm