

Agilent 34138A Test Lead Set

Operating Instructions

This Test Lead Set is designed for use with the Agilent 34xxxA Multimeters, and also the U2741A, U3401A, and U3402A Multimeters. Do not use with the Agilent 3458A.

Assistance

For technical assistance, contact your nearest Agilent Sales Office. Or visit the Agilent web site at **www.agilent.com/find/assist** for further information.

Agilent Technologies, Inc.
900 S. Taft Avenue
Loveland, CO 80537 U.S.A.

Symbols



Refer to instrument manual for additional safety information.

CAT II IEC Measurement Category II. Refer to instrument manual for additional information.

Ratings

Quantity

Test Leads – 1000V, 15A	2 pieces
Fine Tip Probe Attachments – 300V, 3A	2 pieces
Mini Grabber Attachment – 300V, 3A	1 piece
SMT Grabber Attachments – 300V, 3A	2 pieces

Operation

- Refer to the multimeter user's guide for further information.
- The Fine Tip, Mini Grabber, and SMT Grabber attachments plug onto the probe end of the Test Leads.

WARNING: If Test Lead Set is used in a manner not specified by Agilent Technologies, the protection provided by the Test Lead Set may be impaired. *Instrument damage or personal injury may result.*

Maintenance

If any portion of the Test Lead Set is worn or damaged, do not use; replace with a new Test Lead Set.



Agilent Technologies



E0213

34138-90000