


# MALE PCB PINS

## WRAPOST TERMINALS

### 1096

1096-X-05-XX-00-00-01-0

Press-fit in .057 mounting hole




| Basic Part Number | # of Wraps | Length A |
|-------------------|------------|----------|
| 1096-2            | 2          | .381     |
| 1096-3            | 3          | .527     |

### 1106

1106-X-23-XX-00-00-01-0

Press-fit in .057 mounting hole




| Basic Part Number | # of Wraps | Length A |
|-------------------|------------|----------|
| 1106-2            | 2          | .370     |
| 1106-3            | 3          | .510     |

### 1093

1093-0-05-XX-00-00-01-0


Press-fit in .056 mounting hole



### 0730

0730-3-05-XX-00-00-01-0


Press-fit in .057 mounting hole



### 1122

1122-0-22-XX-00-00-01-0


Press-fit in .053 mounting hole



### 1064

1064-0-23-XX-00-00-01-0


Press-fit in .056 mounting hole



### 1092

1092-0-05-XX-00-00-01-0


Press-fit in .056 mounting hole



### 1068

1068-0-23-XX-00-00-01-0


Press-fit in .057 mounting hole



### 1070⇒1072

107X-X-23-XX-00-00-01-0

Press-fit in .057 mounting hole



| Basic Part Number | # of Wraps | Length A |
|-------------------|------------|----------|
| 1072-1            | 1          | .260     |
| 1071-2            | 2          | .370     |
| 1070-3            | 3          | .510     |

#### SPECIFICATIONS:

**Pin Material:** Brass Alloy 360, 1/2 Hard  
(Except where noted)

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$   
Diameters:  $\pm .002$   
Angles:  $\pm 2^\circ$

RoHS-2  
2011/65/EU

**ORDER CODE:** XXXX - X - XX - XX - 00 - 00 - 01 - 0

**BASIC PART #**

**SPECIFY PIN FINISH:**

- 01 200  $\mu$ " TIN/LEAD OVER NICKEL
- ◆ 80 200  $\mu$ " TIN OVER NICKEL (RoHS)
- ◆ 15 10  $\mu$ " GOLD OVER NICKEL (RoHS)
- ◆ 21 20  $\mu$ " GOLD OVER NICKEL (RoHS)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com