

Boardlock not shown  
in this view

Part Number	Contact Area Plating Finish
K88X-ED-9P-BR	Gold Flash (standard option)
K88X-ED-9P-BR15	15u" Gold (15 option)
K88X-ED-9P-BR30	30u" Gold (30 option)

### Material And Finish

- Shell: Steel, Tin plated
- Insulator: PBT with glass-fiber reinforcement, UL 94V-0 rated, color-black
- Contact Material: Plug - Brass
- Plating Options:
  - (Standard) Gold flash on mating end, tin on termination end with nickel underplate
  - 15: 15 u" Gold on mating end tin on termination end with nickel underplate
  - 30: 30 u" Gold on mating end tin on termination end with nickel underplate

### Electrical Specifications

- Rated Current: 2A
- Rated Voltage: 30V RMS
- Dielectric Withstanding Voltage: 500 V (rms) AC for 1 minute
- Insulation Resistance: more than 1000 Megohm at 500 V DC
- Contact Resistance: 13 milliohm max.
- Temperature Rating: -55°C to +105°C
- Durability: 500 mating cycles min.




Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	02/14/06	New Drawing	R. Aguirre	H. MA	R. Aguirre	02/14/06
A2	1/24/08	ECO# 07-052	WILL H.	H. MA		

# K88X-ED-9P-BR

D-Sub, Vertical, 9 Pin Male, RoHS Compliant, RoHS Compliant

Formed Contacts, w/ Boardlocks



UNITS  
mm