



# Circus

Circus - eminently suitable to withstand the rigors of everyday use in such environments as health spas, beauty salons, clinics and laboratories. The arm and neck construction make Circus extremely flexible and easy to work with as it is easily positioned to the exact requirements of the beautician.



- High frequency electronic ballast
- Flicker-free operation
- 6.5", 3.5- (1.85X) or 5-diopter (2.25X) lens magnification
- Optional 4- or 6-diopter accessory lenses
- Fluorescent light source provides high light output and emits minimum heat
- 3500 lux at focal distance
- Optical quality white crown glass lens
- Allows for maximum light comfort for client
- 42 in. (1143 mm) Spring-balanced arm with 3/4 in. (19.1 mm) steel tubing
- Protective lens cover
- Standard with edge mount bracket
- UL/CUL listed
- Finish: white with grey accents
- 5 year warranty

## RELATED PRODUCTS



AH-Edge Mount Bracket



C-Surface Mount

## CODES

## CIRCUS 3.5-DIOPTER

Article Number	Light Source	Socket	Ilcos	Watt	Total Effect	Weight	Lumen	lm/w	IP	Color Rendition	Mount	Ctn. Colors
17970	T5-C	2Gx13	FSCH	22W	22	11.0	1800	81	20	85	Edge clamp	1 <input type="checkbox"/>

## CIRCUS 5-DIOPTER

Article Number	Light Source	Socket	Ilcos	Watt	Total Effect	Weight	Lumen	lm/w	IP	Color Rendition	Mount	Ctn. Colors
17971	T5-C	2Gx13	FSCH	22W	22	11.0	1800	81	20	85	Edge clamp	1 <input type="checkbox"/>

## LENS DATA

Code	Diopter primary	Total Magnification (x)	Total Magnification (%)	Focal Length (mm)	Lens size primary Lux (mm)
17970	3.50	1.9	188	285.7	0 165
17971	5.00	2.3	225	200.0	5400 165

## ACCESSORIES

## DESIGNATION

6-diopter lens attachment	50209
4-diopter lens attachment	50208
34" Floor Stand with casters and glides	50036
C-Surface Mount Bracket	50005
B-Wall Mount Bracket	50003

