

Spring Clamp Panel Mount

Altech "screwless" spring clamp panel mount terminal blocks are an excellent solution for extremely compact wiring applications.

These terminal blocks are "add-on" type and can be combined to form multi-pole assemblies. The stacked assembly is fitted with mounting end sections on both ends for easy installation on to the panel.

The terminal has marker holding recesses on three sides to accept marking tags. Cross connection can be achieved with the aid of insulated jumpers.

The CSCP2.5T2 panel mount terminal blocks have two connection points on each side all with the same potential. The terminals provide possibility of further multiplication through jumpering.



COLOR BLOCKS (other than standard grey)		
When ordering please add color suffix to Cat. No.		
Example for color Red: Cat.No./R		
Color	Ordering Suffix	
Red	R	
Yellow	Y	
Blue	BU	
Green	G	
Consult Altech for availability:		
Orange	O	
Beige	BG	
Dark Brown	DB	
Black	BL	
White	W	



CSCP2.5T



CSCP2.5T2



Terminal Width	5 mm			10 mm		
Height x Length	27 x 35 mm			27 x 35 mm		
Stripping Length	11 mm			11 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 spring clamp connections			4 spring clamp connections		
Approvals						
Wire Range	22-14 AWG	0.2-2.5 sq.mm	22-14 AWG	22-14 AWG	0.2-2.5 sq.mm	22-14 AWG
Voltage Rating	600 V	800 V	600 V	600 V	800 V	600 V
Current Rating	20 A	24 A	20 A	20 A	24 A	20 A
Other Approvals						

Terminal Block

	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.
End Section (set of left and right)	EPCSCP2.5T	25		EPCSCP2.5T	25
Insulated Jumper (2 pole)	CA803/1	100		CA803/1	100
Marking Tags	MT4	100		MT3	100
Operating Tool	SCA2-5	1		SCA2-5	1

Operating Tool
for use with
CSCP2.5T2

