


DRAWING

 General tolerances : ± 0.5 mm

R. F. CHARACTERISTICS

FREQUENCY RANGE : DC - 4 GHz
 IMPEDANCE : 50Ω
 ATTENUATION NOMINAL : 6 dB

FREQUENCY	DC - 2 GHz	2 - 4 GHz
V.S.W.R.	≤ 1.20	≤ 1.30
DEVIATION (dB)	+ 0.3 / - 0.3	+ 0.5 / - 0.5


TEMPERATURE SENSITIVITY : $4 * (10^{-4} \text{ dB} / \text{dB} * ^\circ\text{C})$
 AVERAGE POWER HANDLING at 25° : 1 W
 PEAK POWER HANDLING($1\mu\text{s}$, 1%) at 25° C : 100 W

MECHANICAL CHARACTERISTICS

CONNECTORS : 7/16 male / female per IEC 169-4
 WEIGHT : ≤ 205 g

ENVIRONNEMENTAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE ($^\circ\text{C}$) : - 40 ; + 85
 STORAGE TEMPERATURE RANGE ($^\circ\text{C}$) : - 40 ; + 85

 Power derating
 Versus temperature


CREATION						RADIAL
N°:						101, rue P. Hoffmann
PEN/EP : H920016						93116 ROSNY/BOIS
Name:M.G.						France
Date:24 Apr.96	2 jun 99	New connector body	MG	AF		Tel : (33) 0149353535
Appr.: AF.	Issue	Revisions	Name	Appr.		Fax : (33) 0148546363