

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0387206325](#)
Status: **Active**
Description: 9.53mm (.375") Pitch Beau™ PCB Terminal Strip, without Mounting Ends, 25 Circuits

Documents:

[3D Model](#) [Product Specification PS-38710-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family Terminal Blocks
Series [38720](#)
Application Wire-to-Board
Component Type One Piece
Product Name Fixed Mount Barrier
Type Barrier Strip

Physical


Circuits (Loaded) 25
Circuits (maximum) 25
Color - Resin Black
Entry Angle Horizontal
Lock to Mating Part None
Material - Metal Brass
Material - Plating Mating Tin
Material - Plating Termination Tin
Material - Resin Polyester
Number of Rows 1
Orientation Horizontal
PC Tail Length (in) 0.190 In
PC Tail Length (mm) 4.80 mm
PCB Retention None
PCB Thickness Recommended (in) 0.125 In
PCB Thickness Recommended (mm) 3.18 mm
Panel Mount No
Pitch - Mating Interface (in) 0.375 In
Pitch - Mating Interface (mm) 9.53 mm
Pitch - Term. Interface (in) 0.375 In
Pitch - Term. Interface (mm) 9.53 mm
Plating min: Mating (µin) 150
Plating min: Mating (µm) 3.75
Plating min: Termination (µin) 150
Plating min: Termination (µm) 3.75
Polarized to Mating Part No
Shrouded Dual-Barrier
Stackable No
Surface Mount Compatible (SMC) No
Temperature Range - Operating -40°C to +130°C
Wire Size AWG 14, 16, 18, 20, 22
Wire Size mm² 0.50 - 1.50

Electrical

Current - Maximum per Contact 15A
Voltage - Maximum 300V

Material Info

Old Part Number 72525-C



EU RoHS

**ELV and RoHS
Compliant**
**REACH SVHC
Not Reviewed**
**Halogen-Free
Status**

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

Search Parts in this Series
[38720Series](#)

Mates With
N/A






Reference - Drawing Numbers

Product Specification
Sales Drawing

PS-38710-001
SD-38720-002

This document was generated on 04/23/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION




NOTES:

1. MATERIAL: SEE TABLE
2. FINISHES: SEE TABLE
3. PRODUCT SPECIFICATION: UL & CSA CLASS B & C
4. PACKAGING: NOT REQUIRED
5. MATES WITH: NONE
6. "XX" REFERS TO QTY. OF CIRCUITS
7. INCH DIMS SHOWN IN PARENTHESES (XXI)

6	XX	#6-32 BHD, PHIL.-SLOTTED SCREW WRD	STEEL	ZINC CLEAR CHROMATE
5	XX	#6-32 PHIL.-SLOTTED SCREW W/WASHER	STEEL	ZINC CLEAR CHROMATE
4	XX	#6-32 BHD PHIL.-SLOTTED SCREW	BRASS	NICKEL PLATED
3	XX	#6-32 SCREW PHIL.-SLOTTED	STEEL	ZINC CLEAR CHROMATE
2	XX	TERMINAL	BRASS	TIN PLATED
1	1	BARRIER	THERMOPLASTIC	BLACK
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

EC NO. RELEASED WH 11/11/03 DRN: CHYK: APPR: A	QUALITY SYMBOLS MAJOR CRITICAL SPC S	GENERAL TOLERANCES (UNLESS SPECIFIED) 1 PLACES ±.0015 2 PLACES ±.005 3 PLACES ±.01 4 PLACES ±.03 ANGULAR: ±2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SCALE 2:1 DESIGN UNITS ☐ mm ☒ INCH	THIRD ANGLE PROJECTION ☒ THIRD ANGLE PROJECTION	PROJECT NO. - DIMENSIONS: ☒ INCH ☐ INCH ☐ INCH ONLY SHEET REV REVISE ON CAD ONLY
		DRAWN BY & DATE W. HOWARD 11/11/03 CHECKED BY & DATE APPROVED BY & DATE		TITLE: SR, BTS, NO MTG, PC ASSY		
		CAD FILENAME 725XX-C		MATERIAL NO. SEE TABLE DRAWING NO. SD-38720-002 SHEET NO. 1 OF 2		
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				SIZE B

MATERIAL NO. (OPT -C, -47)	MATERIAL NO. (OPT -C, -50)	MATERIAL NO. (OPT -C, -49)	MATERIAL NO. (OPT -C)	NUMBER OF CIRCUITS "XX"	DIM. "A"	DIM. "B"
38720-8102	38720-7502	38720-6902	38720-6302	02	21.1 (1.83)	9.53 (1.375)
38720-8103	38720-7503	38720-6903	38720-6303	03	30.7 (1.21)	19.05 (1.750)
38720-8104	38720-7504	38720-6904	38720-6304	04	40.1 (1.58)	28.58 (1.125)
38720-8105	38720-7505		38720-6305	05	49.8 (1.96)	38.10 (1.500)
38720-8106	38720-7506	38720-6906	38720-6306	06	59.2 (2.33)	47.63 (1.875)
	38720-7507	38720-6907	38720-6307	07	68.8 (2.71)	57.15 (2.250)
38720-8108	38720-7508	38720-6908	38720-6308	08	78.3 (3.08)	66.68 (2.625)
38720-8109	38720-7509	38720-6909	38720-6309	09	87.8 (3.46)	76.20 (3.000)
38720-8110	38720-7510	38720-6910	38720-6310	10	97.3 (3.83)	85.73 (3.375)
	38720-7511	38720-6911	38720-6311	11	106.9 (4.21)	95.25 (3.750)
38720-8112	38720-7512	38720-6912	38720-6312	12	116.3 (4.58)	104.78 (4.125)
	38720-7513	38720-6913	38720-6313	13	126.0 (4.96)	114.30 (4.500)
38720-8114	38720-7514	38720-6914	38720-6314	14	135.3 (5.33)	123.83 (4.875)
	38720-7515	38720-6915	38720-6315	15	145.0 (5.71)	133.35 (5.250)
38720-8116	38720-7516	38720-6916	38720-6316	16	154.4 (6.08)	142.88 (5.625)
	38720-7517	38720-6917	38720-6317	17	164.1 (6.46)	152.40 (6.000)
	38720-7518	38720-6918	38720-6318	18	173.5 (6.83)	161.93 (6.375)
	38720-7519		38720-6319	19	183.1 (7.21)	171.45 (6.750)
	38720-7520	38720-6920	38720-6320	20	192.5 (7.58)	180.98 (7.125)
	38720-7521		38720-6321	21	202.2 (7.96)	190.50 (7.500)
	38720-7522	38720-6922	38720-6322	22	211.6 (8.33)	200.03 (7.875)
	38720-7523		38720-6323	23	221.2 (8.71)	209.55 (8.250)
	38720-7524		38720-6324	24	230.6 (9.08)	219.08 (8.625)
	38720-7525		38720-6325	25	240.3 (9.46)	228.60 (9.000)
	38720-7526		38720-6326	26	249.6 (9.83)	238.13 (9.375)



EC NO. SEE SH1 DRN: CHK: APPR: A	QUALITY SYMBOLS MAJOR CRITICAL SPC	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE 2:1	DESIGN UNITS ☐ MM ☒ INCH	THIRD ANGLE PROJECTION TITLE: SR, BTS, NO MTG, PC ASSY MOLEX INCORPORATED MATERIAL NO. SEE TABLE DRAWING NO. SD-38720-002 SHEET NO. 2 OF 2	
		1 PLACES	±.0015	±.0015	DRAWN BY & DATE W. HOWARD 11/11/03		
		3 PLACES	±.038	±.005	CHECKED BY & DATE		
		2 PLACES	±.13	±.01	APPROVED BY & DATE		
		1 PLACE	±.1				
		ANGULAR: ±2°		CAD FILENAME 725XX-C			
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.							