






FCIconnect.com

Copyright FCI

PRODUCT NUMBER
SEE SHT. 2



mat'l. code				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection 	product family LATCH-N-LOK
ltr	ecn no	dr	date	tolerances unless otherwise specified		 INCH/MM scale 1:1 	title
D	V91916	TGD	10/7/99	angles	linear .XX±.01/.3		1X8 LATCH-N-LOK 360° SHIELDED
E	V92065	RGD	10/29/99		linear .XXX±.005/.13		PLUG CONN. KIT W/O PV'S
F	V01017	TFG	5/15/00	0°±2°	.XXXX±.0020/.051		
G	V01050	TFG	6/5/00	dr	M. HERNANDEZ	12/03/04	dwg no
H	V01093	TFG	7/6/00	enrg	M. BARRIOS	12/03/04	sheet 1 of 3 size
J	M04-0229	MHT	12/03/04	chr	M. BARRIOS	12/03/04	74903 A3
K	M06-0365	AGS	9/20/06	appd	M. BARRIOS	12/03/04	type Product Customer Drawing
sheet	revision	K	K	K			
index	sheet	1	2	3			

74903-TUVLF


U	COLOR	
01	LT-GRAY	OBS
02	OFF WHITE	
03	DK. GRAY	OBS
04	BLACK	
05	SLATE GRAY	OBS
07	SILVER GRAY	
08	PEARL WHITE	OBS
09	PEBBLE GRAY	

T	HOLE DIA.
7	.265/6.73
9	.312/7.92


EXAMPLE

74903-707LF: IS A 1x8 REAR EXIT PLUG
IN SILVER GRAY WITH A CABLE EXIT
HOLE SIZE OF .265 [6.73] CABLE RANGE ,


mat'l. code				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family LATCH-N-LOK			
ltr	ecn	no	dr	date	tolerances unless otherwise specified				INCH/MM scale 1:1	title 1X8 LATCH-N-LOK 360° SHIELDED PLUG CONN. KIT W/O PV'S dwg no 74903 sheet 2 of 3 size A3 type Product Customer Drawing			
K					angles	linear	.XX±.01/.3 .XXX±.005/.13 .XXXX±.0020/.051						
					0°±2'								
					dr	M. HERNANDEZ	12/03/04						
				enr	M. BARRIOS	12/03/04							
				chr	M. BARRIOS	12/03/04							
				app	M. BARRIOS	12/03/04							
sheet index	revision sheet												



REAR CAP




MINI
LATCH
HOUSING



TOP
SHIELD

BOTTOM
SHIELD



PLUG FRONT

NOTES:

- ① EACH KIT CONTAINS ONE EACH OF THE FOLLOWING COMPONENTS
LATCH-N-LOK PLUG
LATCH-N-LOK END CAP
MINI LATCH HOUSING
360° SHIELD CANS.
2. COMPONENTS ARE BULK PACKAGED WITH 100 pcs. OF A COMPONENT PER BAG. PVC's MUST BE ORDERED SEPARATELY.
3. MATERIALS USED: PLUGS AND CAPS ARE MOLDED IN POLYCARBONATE. THE MINI LATCH HOUSING ARE MOLDED IN NYLON. COLOR IS BLACK. THE SHIELD CAN IS 3/4 HARD BRASS PLATED WITH 2.5um MIN. BRIGHT TIN. 1.0um MIN. NICKEL UNDERPLATE.
- ④ DIMENSIONS ARE APPROXIMATE AND REFLECT PLUG IN UNLATCHED STATE.
5. PART NUMBERS WITH LF IN THE END ARE LEAD FREE.
6. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.



FCIconnect.com

Copyright FCI

mat'l. code				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family LATCH-N-LOK
ltr	ecn	no	dr	date	tolerances unless otherwise specified	scale 1:1 FCI	title
K					angles .XX±.01/.3		1X8 LATCH-N-LOK 360° SHIELDED
					linear .XXX±.005/.13		PLUG CONN. KIT W/O PV'S
					0'±2' .XXX±.0020/.051		
				dr	M. HERNANDEZ 12/03/04		dwg no
				enr	M. BARRIOS 12/03/04		sheet 3 of 3 size
				chr	M. BARRIOS 12/03/04		74903 A3
				app	M. BARRIOS 12/03/04		type Product Customer Drawing
sheet index	revision sheet						