



All dimensions are in mm; tolerances according to ISO 2768 c-H

Available variants

Type	Length "A" (mm)	Insertion loss ≤ (dB) at 26.5 GHz	Weight (g) / pce
LU7-035-800	800	1.90	400
LU7-035-600	600	1.50	350

Documents

Technical data sheet connector left	RPC-3.50 ruggedized jack	03KR123-2U7S3
Technical data sheet connector right	RPC-SL 26.5 GHz jack	04K123-2U7S3
Technical data sheet cable	RTK 162	

Assembly parts

Connector left	RPC-3.50 ruggedized jack	03KR123-2U7S3
Connector right	RPC-SL 26.5 GHz jack	04K123-2U7S3
Cable	RTK 162	
Armour	Metal tubing with fixed bending rate and protection braid	

TECHNICAL DATA SHEET

Rosenberger

CABLE ASSEMBLY
RPC-3.50 JACK / RPC-SL 26.5 GHZ JACK

LU7-035-XXX

Electrical data

Impedance	50 Ω
Frequency	DC to 26.5 GHz
Return loss	≥ 26 dB, DC to 4 GHz ≥ 20 dB, 4 GHz to 26.5 GHz
Insertion loss	see table available variants
Phase deviation:	
After 90° bending	$\leq 1.0^\circ$, DC to 4 GHz $\leq 3.0^\circ$, 4 GHz to 26.5 GHz
Straight after 3x90° bending	$\leq 0.5^\circ$, DC to 4 GHz $\leq 1.5^\circ$, 4 GHz to 26.5 GHz
Amplitude stability	≤ 0.03 dB, DC to 4 GHz ≤ 0.05 dB, 4 GHz to 26.5 GHz
Return loss stability	≥ 48 dB, DC to 4 GHz ≥ 40 dB, 4 GHz to 26.5 GHz
RF-leakage	≥ 100 dB up to 1 GHz

Mechanical data

Minimum bend radius	60 mm
---------------------	-------

Environmental data

Temperature range 2002/95/EC (RoHS)	-40°C to +85°C compliant
--	-----------------------------

Packing

Standard	1 pce in box
----------	--------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Herbert Babinger	15/02/06	Frank Tatzel	29/04/10	e00	11-0169	Krautenbacher J.	28/02/11
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de			Page 2 / 2