





PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			3400	MHz
Upper Frequency:	3400			MHz
Tuning Voltage:	0.3		4.9	VDC
Supply Voltage:	4.75	5.0	5.25	VDC
Output Power:	+3.0		+7.0	dBm
Supply Current:		30	35	mA
Harmonic Suppression (2 nd Harmonic):		-15	-10	dBc
Pushing:		0.1		MHz/V
Pulling, all Phases:		0.3		MHz pk-pk
Tuning Sensitivity:		10		MHz/V
Phase Noise @ 10kHz offset:			-112	dBc/Hz
Phase Noise @ 100kHz offset:			-132	dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			22	pF
Operating Temperature Range:	-40		+85	°C
Storage Temperature Range:	-45		+90	°C

Phase Noise (1 Hz BW, Typical)




Tuning Curve (Typical)




Product Control:

Crystek Part Number:	CVCO55CC-3400-3400	Release Date:	16-Apr-2015
Revision Level:	A	Responsible:	C. Vales





TAPE AND REEL



Drawing not to scale

Product Control:

Crystek Part Number:	CVCO55CC-3400-3400	Release Date:	16-Apr-2015
Revision Level:	A	Responsible:	C. Vales

Specification is subject to change without notice

