Product datasheet Characteristics

9001KYK325



Device short name	ΚY
Enclosure type	Weatherproof enclosure dust and oil resistant indoor/outdoor
Mounting diameter	1.18 in (30 mm)
Provided equipment	Legend plate 1 KN202 Contact block 3 KA1 Legend plate 1 KN210 Legend plate 1 KN211
Complementary	
Line Rated Current	10 A
Contacts type and composition	3 NO + 3 NC
Control type	Push-button 1 9001KR3R Push-button 2 9001KR1B
Device mounting	Surface
Electrical connection	Screw clamp terminal
Enclosure material	Die cast zinc alloy grey
Marking	UP-DOWN-STOP
Operator profile	3 projecting push-buttons
Permissible voltage	<= 300 V
Environment	
NEMA degree of protection	NEMA 3/4/13
product certifications	CE CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR
Offer Sustainability	
Green Premium product	Green Premium product
Compliant - since 1002 - Schneider Electric declaration of conformity	Compliant - since 1002 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals	WARNING: This product can expose you to chemicals including:

Nickel compounds, which is known to the State of California to cause cancer, and California to cause cancer, and

Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period

including:

18 months

