

Product Summary (@T_A = +25°C)

| V _{RRM} (V) | I _o (A) | V _F Max (V) | I _R Max (mA) |
|----------------------|--------------------|------------------------|-------------------------|
| 60 | 5 | 0.52 | 0.22 |


Description

Packaged in the compact thermally efficient POWERDI[®]5 package, the SBR5E60P5 provides ultra-low forward-voltage drop (V_F) and excellent low reverse leakage stability at high temperatures.

Applications

It is ideal for use as a rectification, freewheeling or polarity protection diode in applications such as:

- >10W AC-DC Adaptors/Chargers
- DC-DC Converters




Features and Benefits

- Patented Super Barrier Rectifier SBR[®] technology provides superior avalanche capability versus Schottky diodes, ensuring more rugged and reliable end applications
- Ultra Low Forward Voltage Drop (V_F) Helps Minimize Power Losses
- Excellent Reverse Leakage (I_R) Stability at Higher Temperatures
- Thermally Efficient Package for Cooler Running Applications
- Less Than 1.1mm Package Profile Ideal for Thin Applications
- Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- Halogen and Antimony Free. "Green" Device (Note 3)**

Mechanical Data

- Case: POWERDI[®]5
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: See Diagram Below
- Weight: 0.093 grams (Approximate)




Note: Pins Left & Right must be electrically connected at the printed circuit board.

Ordering Information (Note 4)

| Part Number | Case | Packaging |
|------------------------|------------------------|-------------------|
| SBR5E60P5-13 | POWERDI [®] 5 | 5,000/Tape & Reel |
| SBR5E60P5-13D (Note 5) | POWERDI [®] 5 | 5,000/Tape & Reel |
| SBR5E60P5-7 | POWERDI [®] 5 | 1,500/Tape & Reel |
| SBR5E60P5-7D (Note 5) | POWERDI [®] 5 | 1,500/Tape & Reel |

- Notes:
- EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant. All applicable RoHS exemptions applied.
 - See http://www.diodes.com/quality/lead_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
 - Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
 - For packaging details, go to our website at <http://www.diodes.com/products/packages.html>.
 - POWERDI[®]5 available in 5K quantity on 13-inch reel & 12mm tape, part number suffix "13D"; 1.5K quantity on 7-inch reel, part number suffix "7". Diodes also provides 12mm tape with 7-inch reel, part number suffix "7D".

Marking Information



S5E60 = Product Type Marking Code
 YYWW = Date Code Marking
 YY = Last Two Digits of Year (ex: 15 = 2015)
 WW = Week (01 to 53)
 K = Factory Designator

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

| Characteristic | Symbol | Value | Unit |
|--|------------------|-------|------|
| Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage | V _{RRM} | 60 | V |
| Average Rectified Output Current | I _O | 5 | A |
| Non-Repetitive Peak Forward Surge Current 8.3mS | I _{FSM} | 170 | A |

| Parameter | Symbol | Value | Unit |
|---------------------------------|---------|-------|------|
| Human Body Model ESD Protection | ESD HBM | 8 | kV |
| Machine Model ESD Protection | ESD MM | 400 | V |

Caution: Stresses greater than the 'Absolute Maximum Ratings' specified above, may cause permanent damage to the device. These are stress ratings only; functional operation of the device at these or any other conditions exceeding those indicated in this specification is not implied. Device reliability may be affected by exposure to absolute maximum rating conditions for extended periods of time..
Semiconductor devices are ESD sensitive and may be damaged by exposure to ESD events. Suitable ESD precautions should be taken when handling and transporting these devices.






Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|---|-----------------------------------|-------------|------|
| Typical Thermal Resistance Junction to Ambient (Note 6) | R _{θJA} | 22 | °C/W |
| Typical Thermal Resistance Junction to Case (Note 6) | R _{θJC} | 3 | °C/W |
| Operating and Storage Temperature Range | T _J , T _{STG} | -55 to +150 | °C |

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|--------------------------|----------------|-----|------|------------|------|---|
| Forward Voltage Drop | V _F | — | 0.33 | — | V | I _F = 1A, T _A = +25°C |
| | | — | 0.45 | 0.52 | | I _F = 5A, T _A = +25°C |
| | | — | 0.24 | — | | I _F = 1A, T _A = +125°C |
| | | — | — | 0.5 | | I _F = 5A, T _A = +125°C |
| Leakage Current (Note 7) | I _R | — | — | 0.22 50 | mA | V _R = 60V, T _A = +25°C V _R = 60V, T _A = +125°C |

Notes: 6. Device mounted on 2inch*2inch Al board.
7. Short duration pulse test used to minimize self-heating effect.




Package Outline Dimensions

Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for the latest version.

NEW PRODUCT

POWERDI[®]5




| POWERDI [®] 5 | | | |
|------------------------|------|------|-------|
| Dim | Min | Max | Typ |
| A | 1.05 | 1.15 | 1.10 |
| A1 | 0.00 | 0.05 | — |
| A2 | 0.33 | 0.43 | 0.381 |
| b1 | 0.80 | 0.99 | 0.89 |
| b2 | 1.70 | 1.88 | 1.78 |
| D | 3.90 | 4.05 | 3.966 |
| D2 | — | — | 3.054 |
| E | 6.40 | 6.60 | 6.504 |
| e | — | — | 1.84 |
| E1 | 5.30 | 5.45 | 5.37 |
| E2 | — | — | 3.549 |
| L | 0.75 | 0.95 | 0.85 |
| L1 | 0.50 | 0.65 | 0.57 |
| W | 1.10 | 1.41 | 1.255 |
| All Dimensions in mm | | | |

Suggested Pad Layout

Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.

POWERDI[®]5



| Dimensions | Value (in mm) |
|------------|---------------|
| C | 1.840 |
| G | 0.852 |
| X | 1.390 |
| X1 | 3.360 |
| Y | 1.400 |
| Y1 | 4.860 |

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2015, Diodes Incorporated

www.diodes.com