






HET400PA series

Dimension drawing



| Main feature | Unit | Model Number |
|---------------------------|------|-----------------------|
| | | HET400PA |
| Outline dimension | mm | 450 H x 210 W x 228 D |
| Weight | kg | 11.0 ± 0.5 |
| Cooling capacity (△T =0℃) | w | 400 (TYP.) |
| Heating capacity @ -40° C | w | 450 (TYP.) |
| Rated voltage | VDC | 48 (TYP.) |
| Operating voltage range | VDC | 40~56 |
| Actuality Current | Α | 11.7(TYP.) |
| Power Consumption | w | 562 |
| Operating temperature | °C | -40~55 |
| Internal airflow rate | CFM | 190 (TYP.) |
| External airflow rate | | 200 (TYP.) |
| Acoustic noise at 1M: | dB-A | 65.0 (TYP.) |
| (Sound pressure) | | 69.0 (Max.) |

* Specifications are subject to change without

notice

Features

- ♦ IP55 waterproof at external side
- ◆ FAN / TEC / Control fail alarm
- ♦ Clear LED status indicator
- ◆ Standalone temperature control
- ♦High efficiency and reliable fan modules

Design

- ♦ High efficiency of cooling & Heating
- ◆ Thermal electric cooling module
- ♦ Rated voltage at 48V
- ♦ Built-in controller