

CONFIGURATION		PART NUMBER
Male Receptacle, 4 Pin, 3.6mm, Shell 16		RT00164PNH
DIMENSIONS		
<p>Technical drawings of the RT360 connector showing dimensions and components.</p> <p>Left drawing: Cross-section view showing O-Ring, Insert, Shell, and Seal Gasket. Dimensions: Ø 23.60, 26.9, 11.30, 1.80, 25.30. Thread: UNEF 15/16-20 THREAD.</p> <p>Middle drawing: Front view showing MASTER KEYWAY, 4-Ø 3.20 pins, and dimensions 31.0, 24.60, 24.60.</p> <p>Right drawing: Side view of the connector.</p> <p>Bottom drawing: PANEL CUT OUT REFERENCE showing dimensions 24.60, Ø 24.60 (For Front Panel Mounting), Ø 28.10 (For Rear Panel Mounting), and 4-Ø 3.30.</p>		
TECHNICAL DATA		
TEMPERATURE RANGE:	-40°C to + 105°C	
PROTECTION:	IP67 in mated condition and in combination with sealed backshell	
VOLTAGE RATING:	400v	
HOUSING BODY:	Zinc Alloy, Nickel Plated	
COUPLING NUT:		
INSERT:	Glass-filled Thermoplastic UL94-V0	
SEAL:	NBR	
CURRENT:	46A	
CONTACT SIZE:	3.6mm	
APPROVALS:	UL ECBT2	