


PRODUCT NUMBER
SEE TABLE, SHEET 5




rev	ecn no	dr	date
H	S09-0279	YK	2009-09-07
-	-	-	-
C	V04-1194	DAB	2004-12-27
D	V05-0105	TH	2005-02-09
E	V05-0226	MRS	2005-03-10
F	V05-0748	CH	2005-08-23
G	S06-0374	CH	2006-12-21

www.fciconnect.com			surface 3.2 ASME Y14.5	tolerance std ASME Y14.5	projection	MM
			TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	D. BUSH	2004-10-13	ANGULAR LINEAR	0.X	±	size A4 Scale 2:1
Eng	Y. K. LIM	2009-09-07		0.XX	±	
Chr	Y. K. LIM	2009-09-07		0.XXX	±	
Appr	JOEY NG	2009-09-07	Product family AirMax VS			ECN S09-0279
			Spec ref			
FCI			title AirMax VS R/A HEADER ASSY PRESS-FIT, 150 POS, 20MM			Rev. H
			catalog no -			dwg no 10016527
			CUSTOMER			sheet 1 of 5



Copyright FCI.

DESCRIPTION	DIM A	DIM B	DIM C
2-20MM MODULES PLACED END-TO-END	2.00	19.90 2X	20.00
1-20MM MODULE & 1-22MM MODULE PLACED END-TO-END	3.00	19.90 1X & 21.90 1X	21.00




RECOMMENDED PCB LAYOUT
FOR DIFFERENTIAL APPLICATIONS
COMPONENT SIDE
(TWO ADJACENT FOOTPRINTS SHOWN)
NOTES 6 & 7

	title		dwg no		Rev.
	AirMax VS R/A HEADER ASSY		10016527		H
	PRESS-FIT, 150 POS, 20MM				
catalog no		-	CUSTOMER	sheet 2 of 5	



Copyright FCI.

DESCRIPTION	DIM D	DIM E	DIM F
2-20MM MODULES PLACED END-TO-END	2.00	19.90 2X	20.00
1-20MM MODULE & 1-22MM MODULE PLACED END-TO-END	3.00	19.90 1X & 21.90 1X	21.00



DETAIL B

RECOMMENDED PCB LAYOUT
FOR SINGLE ENDED APPLICATIONS
COMPONENT SIDE
(TWO ADJACENT FOOTPRINTS SHOWN)
NOTES 6 & 7

	title	AirMax VS R/A HEADER ASSY		dwg no	10016527		Rev. H
		PRESS-FIT, 150 POS, 20MM					
	catalog no		-	CUSTOMER		sheet 3 of 5	



Copyright FCI.

REV F - 2006-04-17

SEE NOTE 9
 $\varnothing 0.10$
ALL HOLES

GND POSITION
(0.100)

ANTIPAD WIDTH=
 $2.0 - (\text{TRACE} + \text{SPACE} + \text{TRACE})$
TYP

2.00 TYP

3.200
TYP

2.000
C OF POS
2, 4, 6, 8, & 10

1.40 14X
2.100
C OF POS
1, 3, 5, 7, & 9

DETAIL A
SCALE 4:1

ANTIPAD WIDTH=
 $2.0 - (\text{TRACE} + \text{SPACE} + \text{TRACE})$
TYP

2.00 TYP

SEE NOTE 9
 $\varnothing 0.10$
ALL HOLES

GND POSITION
(0.100)

1.800
TYP

1.40 14X

2.100
C OF POS
1, 3, 5, 7, & 9

DETAIL B
SCALE 4:1

2.000
C OF POS
2, 4, 6, 8, & 10



title AirMax VS R/A HEADER ASSY
PRESS-FIT, 150 POS, 20MM
catalog no -

dwg no 10016527
CUSTOMER

Rev. H

sheet 4 of 5

PDM: Rev:H

STATUS:Released


Printed: Nov 30, 2010



Copyright FCI.

PART NUMBER	PRESS-FIT TAIL PLATING TYPE	SHORT DETECT CONTACT
10016527-101	TIN/LEAD ALLOY OVER NICKEL	NO
10016527-101LF	TIN OVER NICKEL (LEAD FREE)	
10016527-111	TIN/LEAD ALLOY OVER NICKEL	YES (SEE NOTE 13)
10016527-111LF	TIN OVER NICKEL (LEAD FREE)	

- NOTES:
1. CONNECTOR MATERIALS:
HOUSING & RETAINER: HIGH TEMP THERMOPLASTIC, NATURAL, UL94V-0
IMLA PLASTIC: HIGH TEMP THERMOPLASTIC, BLACK, UL94V-0
CONTACT: COPPER ALLOY
2. CONTACT PLATING:
SEPARABLE INTERFACE:
PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-239 INCLUDING TELCORDIA GR-1217-CORE (NOVEMBER 1995) CENTRAL OFFICE TEST SEQUENCE
- PRESS-FIT TAILS: SEE TABLE
3. PRODUCT SPECIFICATION: GS-12-239
4. APPLICATION SPECIFICATION: GS-20-035
5. PRODUCT MARKING, (PART NUMBER & LOT CODE), ON THIS SURFACE
6. REFER TO CUSTOMER DRAWING 10035911 FOR INFORMATION REGARDING PCB LAYOUT OF POWER AND GUIDE MODULES RELATIVE TO SIGNAL MODULES
7. POSITIONS F AND L OF ODD NUMBERED COLUMNS AND POSITIONS G AND M OF EVEN NUMBERED COLUMNS CORRESPOND TO EARLY MATE HEADER PINS
8. THERE IS NO GROUND BUSSING WITHIN THE CONNECTOR SYSTEM



9. REFER TO CUSTOMER DRAWING 10045979 FOR INFORMATION ON PCB HOLE DIAMETERS AND PLATING OPTIONS.
10. LEAD FREE PRODUCT MEETS EUROPEAN UNION DIRECTIVES & OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
11. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 40 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
12. PACKAGING MEETS GS-14-920 LEAD FREE LABELING SPECIFICATION.
13. MATING PIN H6 HAS 0.5mm LESS WIPE THAN THE SHORTEST SIGNAL PIN.
14. A  SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.



title	AirMax VS R/A HEADER ASSY PRESS-FIT, 150 POS, 20MM	dwg no	10016527	Rev.	H
catalog no	-	CUSTOMER	sheet 5 of 5		