


Mini Feed-Through 15mm

For wire-to-wire connecting in control, automation, instrumentation and power distribution applications.

Altech "miniature" terminal blocks offer tremendous space advantage as demanded by certain wiring configurations.



Terminal Width	
Height x Length	
Stripping Length	
Insulation Material	
Type of Connection	
Approvals	
Wire Range	
Voltage Rating	
Current Rating	
Torque	
Other Approvals	

Terminal Block

End Plate	
Isolation Partition	
DIN Rail for ordering information refer to page 72	
End Stop for ordering information refer to page 74	

Internal Jumper		2 pole 3 pole 4 pole 10 pole
-----------------	--	---------------------------------------

Insulated Internal Jumper		2 pole 3 pole 4 pole 10 pole
---------------------------	--	---------------------------------------

Current Bars		2 pole 3 pole 4 pole 10 pole 10 pole (breakable) 100 pole
--------------	--	--

Shorting Sleeve & Screw		
-------------------------	--	--


External Jumper		2 pole 3 pole 4 pole 10 pole
-----------------	--	---------------------------------------

Marking Tags (MT Type)		
(MT Type on Lever)		

CMT4



6 mm		
29 x 27 mm		
9 mm		
Polyamide 6.6		
2 screw clamps & 1 tapped hole for cross connection		
22-10 AWG	0.5-4 sq.mm	22-10 AWG
300 V	400 V	300 V
35 A	32 A	35 A
6 lb-in	0.5 Nm	7 lb-in



Cat. No.	Std. Pk.
----------	----------

CMT4	100
EPCMT4	50
PPCMT4	50



CA602	100
-------	-----

CA727/2	100
CA727/3	100
CA727/4	100
CA727/10	10

CA747/2	100
CA747/3	100
CA747/4	100
CA747/10	10

CA703/1	100
CA704/1	100
CA705/1	100
CA732/10	100
CA732/10-A	100
CA732/100	10

CA607/S/Q	100
-----------	-----

CA714/2	100
CA714/3	100
CA714/4	100
CA714/10	20

MT2	100
-----	-----

CGMT4



6 mm		
28.5 x 27 mm		
9 mm		
Polyamide 6.6		
2 screw clamps		
22-10 AWG	0.5-4 sq.mm	22-10 AWG
	32A	
7 lb-in	0.5 Nm	7 lb-in



Cat. No.	Std. Pk.
----------	----------

CGMT4	50
--------------	----



--	--

--	--

--	--

--	--

--	--

--	--

MT2	100
-----	-----

COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB