




CXG2.5/3

CXG2.5/4

CXG4/3



Dimensions

| | | | |
|-------------------|---------------------------|--------------------|--------------------|
| Width | 5 mm | 5 mm | 6 mm |
| Length | 62.2 mm | 74.7 mm | 70.5 mm |
| Height w DIN Rail | 35 x 7.5 mm 35 x 15 mm | 38.0 mm 45.5 mm | 38.0 mm 45.5 mm |

Technical Data/Ratings

| | | | |
|------------------------------|--|--|--|
| Approvals | | | |
| Wire Size (solid stranded) | 24-12 AWG 0.2-2.5 mm ² | 24-12 AWG 0.2-2.5 mm ² | 24-10 AWG 0.2-4 mm ² |
| Voltage Rating | 600 V 1000 V | 600 V 1000 V | 600 V 1000 V |
| Current Rating | - | - | - |
| Insulation Material | Polyamide 66 | Polyamide 66 | Polyamide 66 |

Installation Instructions

| | | | |
|-----------------------|----------|------------|------------|
| Wire Stripping Length | 10 mm | 10 mm | 10 mm |
| Screwdriver | 0.5x3 mm | 0.6x3.5 mm | 0.6x3.5 mm |

Terminal Blocks

| | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. |
|-----------------------|-----------------|----------|-----------------|----------|---------------|----------|
| Yellow / Green | CXG2.5/3 | 100 | CXG2.5/4 | 50 | CXG4/3 | 50 |

Accessories


| | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. |
|---------------------------|--|-----------------------|--|-----------------------|--|-----------------------|
| End Plate | EPCX2.5/3 | 50 | EPCX2.5/4 | 20 | EPCX4/3 | 20 |
| Partition Plate | PPCX4/3 | 20 | PPCX4/4 | 20 | PPCX4/3 | 20 |
| DIN Rail | 2511120 CA701-15/S | 20 10 | 2511120 CA701-15/S | 20 10 | 2511120 CA701-15/S | 20 10 |
| End Stop | CA702 CA802 CA103 | 50 50 50 | CA702 CA802 CA103 | 50 50 50 | CA702 CA802 CA103 | 50 50 50 |
| Shorting Link/ Jumpers | 2 pole JX2.5/2 3 pole JX2.5/3 4 pole JX2.5/4 10 pole JX2.5/10 | 100 50 50 10 | 2 pole JX4/2 3 pole JX4/3 4 pole JX4/4 10 pole JX4/10 | 100 50 50 10 | 2 pole JX6/2 3 pole JX6/3 4 pole JX6/4 10 pole JX6/10 | 100 50 50 10 |
| Warning Label | WLX2.5 | 100 | WLX2.5 | 100 | WLX4 | 100 |
| Test Plug | TX2.5 | 50 | TX2.5 | 50 | TX4 | 50 |
| Marking Tag | MT5 | 100 | MT5 | 100 | MT6 | 100 |

CX SERIES

SPRING TERMINAL BLOCKS

MULTIPLE CONNECTION GROUND / EARTH TERMINAL BLOCKS

CXG4/4



CXG6/3



CXG10/3



Dimensions

| | | | |
|-------------------|---------------------------|--------------------|--------------------|
| Width | 6 mm | 8 mm | 10 mm |
| Length | 86.2 mm | 82.2 mm | 82.2 mm |
| Height w DIN Rail | 35 x 7.5 mm 35 x 15 mm | 38.0 mm 45.5 mm | 43.0 mm 50.5 mm |

Technical Data/Ratings

| | | | | | | |
|------------------------------|--------------|-----------------------|--------------|-----------------------|--------------|------------------------|
| Approvals | | | | | | |
| Wire Size (solid stranded) | 24-10 AWG | 0.2-4 mm ² | 24-8 AWG | 0.2-6 mm ² | 24-6 AWG | 0.2-10 mm ² |
| Voltage Rating | 600 V | 1000 V | 600 V | 1000 V | 600 V | 1000 V |
| Current Rating | - | - | - | - | - | - |
| Insulation Material | Polyamide 66 | | Polyamide 66 | | Polyamide 66 | |

Installation Instructions

| | | | |
|-----------------------|------------|----------|----------|
| Wire Stripping Length | 10 mm | 10 mm | 18 mm |
| Screwdriver | 0.6x3.5 mm | 0.8x4 mm | 0.8x4 mm |

Terminal Blocks

| | | | | | | |
|-----------------------|---------------|----------|---------------|----------|----------------|----------|
| | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. |
| Yellow / Green | CXG4/4 | 50 | CXG6/3 | 50 | CXG10/3 | 50 |

Accessories

| | | | | | | | |
|---------------------------|---------------------------------------|-----------------------------------|-------------------------|-----------------------------------|-------------------------|-----------------------|--------------------|
| | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | Cat. No. | Std. Pk. | |
| End Plate | EPCX4/4 | 20 | EPCX6/3 | 20 | EPCX10/3 | 20 | |
| Partition Plate | PPCX4/4 | 20 | - | - | - | - | |
| DIN Rail | 2511120 CA701-15/S | 20 20 | 2511120 CA701-15/S | 20 20 | 2511120 CA701-15/S | 20 20 | |
| End Stop | CA702 CA802 CA103 | 50 50 50 | CA702 CA802 CA103 | 50 50 50 | CA702 CA802 CA103 | 50 50 50 | |
| Shorting Link/ Jumpers | 2 pole 3 pole 4 pole 10 pole | JX4/2 JX4/3 JX4/4 JX4/10 | 100 50 50 10 | JX6/2 JX6/3 JX6/4 JX6/10 | 100 50 50 10 | JX10/2 - - - | 100 - - - |
| Warning Label | WLX4 | 100 | WLX6 | 100 | WLX10 | 100 | |
| Test Plug | TX4 | 50 | TX6 | 50 | TX10 | 50 | |
| Marking Tag | MT6 | 100 | MT8 | 100 | MT10 | 100 | |