

12 Right-Angle Outlet Vertical Power Strip, 120V, 15A, 15-ft. Cord, 5-15P, 36 in.

MODEL NUMBER: PS3612RA









Highlights

- 12 right-angle receptacles
- Convenient and safe covered, on/off switch
- 15-amp circuit breaker
- 15-ft. cord with right angle plug
- 36-in. length

Package Includes

- PS3612RA Power Strip
- Mounting hardware
- Instruction manual

Description

Tripp Lite's PS3612RA power strip offers 15 amp, 120V multi-outlet AC power distribution in a convenient 36 inch mountable housing. Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications. Includes 12 right-angle NEMA 5-15R receptacles with 2.64 inch center-to-center spacing, 15 ft AC line cord and lighted power switch with locking transparent cover to prevent accidental shutoff. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 12 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: 36 in. corded, mountable power strip

Features

- · Sturdy all-metal 36-inch corded strip format with 2.638 inch center-to-center outlet spacing
- Includes 12 right-angle NEMA 5-15R receptacles
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- Lighted power switch with locking transparent cover prevents accidental shutoff
- 15 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications

ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(12) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15	



Outlet Spacing	2.638 in.	
Right-Angle Outlets	Yes	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Connection Type	Right angle Nema 5-15P	
Input Plug Features	Black	
Input Cord Length (ft.)	15	
Input Cord Length (m)	4.572	
Input Cord Gauge Type	14/3 SJT	
Voltage Compatibility (VAC)	120	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Lighted 2 position switch controls power to all outlets	
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
PHYSICAL		
Unit Dimensions (hwd / in.)	1.25 x 1.50 x 36	
Unit Dimensions (hwd / cm)	3.18 x 3.81 x 91.44	
Unit Weight (lbs.)	3.23	
Unit Weight (kg)	1.47	
Material of Construction	Aluminum	
Included Mounting Accessories	Includes mounting clips	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Form Factors Supported	Supports horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications	
Outlets Measurement (Center to Center)	67mm	
CERTIFICATIONS		
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Product Warranty Period (Worldwide)

Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies