

# Solid-state relay module - IEG-OV-S0/120DC/1 - 2964568


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power solid-state relay, for S0 meter interfaces, output: 15 - 120 V DC



## Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 10 pc   |
| GTIN         | <br>4 017918 139254 |
| GTIN         | 4017918139254   |

## Technical data

### Note

|                         |   |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

### Dimensions

|        |       |
|--------|-------|
| Width  | 27 mm |
| Height | 79 mm |
| Depth  | 74 mm |

### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -20 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 60 °C |

### Input data

|                              |                             |
|------------------------------|-----------------------------|
| Typical response time        | 1 ms                        |
| Typical turn-off time        | 1 ms                        |
| Status display               | LED                         |
| Type of protection           | Reverse polarity protection |
|                              | Surge protection            |
| Protective circuit/component | Polarity protection diode   |

# Solid-state relay module - IEG-OV-S0/120DC/1 - 2964568

## Technical data

### Input data

|                          |                 |
|--------------------------|-----------------|
| Transmission frequency   | 10 Hz           |
| Designation              | S0 input        |
| Input current "0" signal | < 2 mA          |
| Input current "1" signal | 10 mA ... 27 mA |

### Output data

|  |                             |
|--|-----------------------------|
| Output voltage range                             | 15 V DC ... 120 V DC        |
| Limiting continuous current                      | 1.5 A (maximum)             |
| Voltage drop at max. limiting continuous current | 1.4 V DC                    |
| Output circuit                                   | 2-wire, floating            |
| Type of protection                               | Reverse polarity protection |
|  | Surge protection            |

### Connection data, input side

|                                  |   |
|----------------------------------|---|
| Connection name                  | Input side                                |
| Connection method                | Screw connection                          |
| Stripping length                 | 8 mm                                      |
| Screw thread                     | M3  |
| Conductor cross section solid    | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
| Conductor cross section flexible | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
| Conductor cross section AWG      | 24 ... 12                                 |

### General

|                      |                             |
|----------------------|-----------------------------|
| Mounting position    | any                         |
| Overvoltage category | III (according to EN 50178) |

### Standards and Regulations

|                               |  |
|-------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
| Noise emission                | EN 61000-6-4                               |
| Noise immunity                | EN 61000-6-2                               |
| Low Voltage Directive         | Conformance with LV directive 2006/95/EC   |
| Conformance                   | CE-compliant                               |

### Environmental Product Compliance

|            |   |
|------------|---|
| REACH SVHC | Lead 7439-92-1  |
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Approvals

### Approvals

## Solid-state relay module - IEG-OV-S0/120DC/1 - 2964568

### Approvals

Approvals


EAC

---

Ex Approvals

---

### Approval details

|     |   |                          |
|-----|---|--------------------------|
| EAC |  | RU C-<br>DE.A*30.B.01082 |
|-----|---|--------------------------|

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>