

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DIST
—	—

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REDRAW PER ECO-11-000539	19JAN11	HMR	MW






INDICATION EXAMPLE


4	F	30
T	T	T
YEAR	MONTH	DAY
2011	01	13




SPECIFICATION:

RATING: 6A 125V AC, 6A 250V AC
(RESISTANCE LOAD)
CONTACT RESISTANCE: 2-4V DC 1A LESS THAN 0.01Ω
INSULATION RESISTANCE: DC 500V OVER 1,000MΩ
DIELECTICAL STRENGTH: INITIAL 1,000V AC 1 MINUTE.
ENDURANCE: ELECTRICAL OVER 25,000 CYCLE.
MECHANICAL OVER 50,000CYCLES
OTHER: GREASE TO USE...GOLD RESISTANT GREASE
(MULTEMP PS NO.1) NOT BUTTON.






P C MOUNTING



TERMINAL



6 5(4)	6 5 4	(6)5 4		
3 2(1)	3 2 1	(3)2 1		
(ON)	(OFF)	(ON)		
CIRCUIT DIAGRAM				

( ) IS MOMENTARY

ITEM NO.	COMPONENT NAME	QUANTITY	MATERIAL	REMARK
8	L-SPRING	1	SUS304 STAINLESS STEEL	-
7	KNOB	1	C3602BD FREE CUTTING BRASS ROD	Ep-Cu/Ni3, AuF b NICKEL PLATED
6	MOUNTING SLEEVE	1	C3602BD FREE CUTTING BRASS ROD	Ep-Cu/Ni3, AuF b NICKEL PLATED
5	PLATE	1	SPCC COLD ROLLED STEEL SHEET	Ep-Fe/Sn2 b TIN PLATED
4	FRAME	1	SUS304 STAINLESS STEEL	-
3	FIXED CONTACT	4	C3602BD FREE CUTTING BRASS ROD	Ep-Cu/Ni3, AuF b GOLD PLATED
2	COMMON	2	C3602BD FREE CUTTING BRASS ROD	Ep-Cu/Ni3, AuF b GOLD PLATED
1	CASE	1	POLYESTER	BLACK

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± -

MATERIAL -
FINISH -

DWN RAGHAVENDRA 19JAN11
CHK WILBOURN MICHEAL 19JAN11
APVD WILBOURN MICHEAL 19JAN11
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

Tyco Electronics
Tyco Electronics Corporation
Harrisburg, PA 17105-3608

NAME SWITCH ROCKET (FES 60)

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1732033	—

CUSTOMER DRAWING | SCALE 1:1 | SHEET 1 OF 1 | REV A

1732033