



**Product:** [83554](#)

Electronic, 4 C #22 Str TC, FEP Ins, OS+TC Brd, FEP Jkt, CMP

[Request Sample](#)

## Product Description

High Temperature Electronic, 4 Conductor 22AWG (7x30) Tinned Copper, FEP Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, FEP Outer Jacket, CMP

## Technical Specifications

### Product Overview

Suitable Applications:	extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring
------------------------	---

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
22	7x30	TC - Tinned Copper	4

Conductor Count:	4
------------------	---

#### Insulation

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.0065 in

#### Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Alum / Poly	Beldfoil®	100 %
Braid	2	TC - Tinned Copper		85 %

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.159 in	0.014 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
15.5 Ohm/1000ft	4.9 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
23 pF/ft	40 pF/ft

## Current

### Max. Recommended Current [A]

2.2 Amps per conductor @ 25°C

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

Operating Temp Range: -70°C To +200°C

## Mechanical Characteristics

Bulk Cable Weight: 25 lbs/1000ft

Max Recommended Pulling Tension: 40 lbs

Min Bend Radius/Minor Axis: 1.75 in

## Standards

NEC Articles: 800

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

CPR Euroclass: Eca

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-04-01

MII Order #39 (China RoHS): Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability: NFPA 262

CSA Flammability: FT6

ISO/IEC Flammability: IEC 60332-1-2

UL voltage rating: 300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N): Yes

## Part Number

### Variants

Item #	Color	Putup Type	Length	UPC
83554 002100	Red	Reel	100 ft	612825204954
83554 002500	Red	Reel	500 ft	612825204978
83554 0021000	Red	Reel	1,000 ft	612825204961

Footnote: C - CRATE REEL PUT-UP.

## Product Notes

Notes: Plenum Cables, except for Flamarrest<sup>®</sup> jacket, are suitable for Outdoor and Direct Burial application.

## History

Update and Revision: Revision Number: 0.292 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.