


DIT IS ONZE EIGENDOM EN MAG NOCH NAGEMAAKT, HERDRUKT, OVERGEMAAKT AAN DERDEN, NOCH VOOR FABRIKATIE GEBRUIKT WORDEN, ZONDER ONZE SCHRIFTELIJKE TOELATING. BIJ NIET GEBRUIK IS DE TERUGZENDING VERPLICHT.

THIS IS OUR EXCLUSIVE PROPERTY. IT IS NOT TO BE COPIED, REPRINTED OR DISCLOSED TO A THIRD PARTY, NOR USED FOR MANUFACTURING WITHOUT OUR WRITTEN CONSENT, AND HAS TO BE RETURNED TO US IN CASE OF NO USAGE

REV.	DATE	DESCRIPTION	BY	C'K'D'
03	10/03/99	Temperature range -55C instead of -25C	K.N.	
04	09/11/05	ADD SIZE 10-3 - ADD 3D VIEW	R Ch	
05	21/01/10	ADD O'SEAL ON THE SECTION VIEW	R Ch	
A	30/10/13	DELETE PART NUMBER UTG1103P(H)VDE	R Ch	

WIRING FACE



CAT. NUMBER	A MAX.	B±0.15	C±0.2	Ø D±0.15	Ø E±0.15
UTG1104P (H)	31.7	5.0	8.65	15.0	19.5
UTG1125P (H)	31.7	5.0	8.65	19.0	23.5
UTG1128P (H)	31.7	5.0	8.65	19.0	23.5
UTG11412P (H)	31.7	5.0	8.65	22.2	27.0
UTG11619P (H)	31.7	5.0	8.65	25.3	30.0
UTG11823P (H)	31.7	5.0	8.65	28.5	33.3
UTG12028P (H)	33.3	5.0	12.05	31.7	36.5
UTG12235P (H)	33.3	5.0	12.05	34.9	39.7
UTG12448P (H)	33.3	5.0	13.85	38.0	42.5
* NOTE 4					

MATERIAL

UTG1128P AS SHOWN

- BODY : GLASS-FILLED POLYESTER UL94-V0
COLOUR : BLACK.
- TRILOK RING : HIGH STRENGTH CuZn ALLOY,
NICKEL PLATED.

PERFORMANCE CHARACTERISTICS

- OPERATING TEMPERATURE : -55°C to +125°C
- INSULATION RESISTANCE : 5000 M Ohm MIN.
- TEST POTENTIAL : 2000 V EFF.

NOTES

- 1.CONNECTOR ACCEPTS # 16 STRIP FORMED PIN, MACHINED PIN
AND SUBMINIATURE COAXIAL PIN AND SOCKET CONTACTS.
- 2.CONTACTS TO BE ORDERED SEPARATELY : REFER TO TRIM - TRIO CATALOG.
- 3.FOR OTHER INSERT ARRANGEMENTS SEE BS,C ,201458,000
- 4.FOR WATERPROTECTED VERSION: ADD "H" TO THE CAT.NO. E.G. CAT.NO.: UTG1128PH

GEN. ST.	01	02	03	04	05	06	07	08	0D	50	60	70	80	90																							
INT. ST.	10	11	12	13	14	18	20	31	32	33	34	38	39	40	42	43	44	45	46	48	56	70	72	73	75	76	81	82	83	84	88						
1DEC ±0,2 1DEC 2DEC ±0,1 2DEC ANGLES ±1° HOEKEN		APPR.		DATE		SIGN.		MALE RECEPTACLE FREE HANGING																													
WE RESERVE THE RIGHT TO CHANGE DIMENSIONS OR REQUIREMENTS WITHOUT PRIOR NOTICE.		DRAFT		7-6-91		M BUEDS		CAT.N°. UTG1---P (H)																													
		CHECKED																																			
ALL DIMENSIONS IN MM		PROD. MGR.						SOURIAU Route Nationale 23 72470 CHAMPAGNE																													
		PR.ENG.MGR.																																			
ALLE AFMETINGEN IN MM		PR.MGT.MGR.						SCALE																													
		REFERENCES																		BS-A-201458-005																	
		DRAWING NR.																		CUSTOMER DRAWING																	

NOT EXPORT CONTROLLED