EXTECH INSTRUMENTS

PRODUCT DATASHEET

IR260 Compact InfraRed Thermometer



Compact non-contact InfraRed (IR) Thermometer measures up to 752ºF (400ºC) with built-in laser pointer to identify target area and improve aim. Adjustable emissivity for better accuracy when measuring temperature on different surface materials.



Test for temperature in HVAC systems



Checking for heat loss around windows and doors



Detect hot spots on circuit breaker panels

Features

- Take non-contact temperature measurements from -4 to 752°F (-20 to 400°C)
- 12:1 distance to spot (target) ratio
- Built-in laser pointer identifies target area with on/off button
- Programmable high/low alarm alerts user visually and audibly when temperature exceeds set limits (audible alarm can be muted)
- Adjustable emissivity for better accuracy on variety of surfaces
- Automatic Data Hold when trigger released
- MAX/MIN function stores maximum and minimum readings with easy recall
- Bright white backlighting illuminates display for taking measurements at night or in areas with low background light levels
- Auto power off ~9 seconds after trigger is released
- Overrange and low battery indicators
- Complete with two AA batteries

Specifications	
IR Temperature Range	-4 to 752°F (-20 to 400°C)
Basic Accuracy	±2% of reading or ±3.6°F/2°C
Max resolution	0.1°F/°C
Distance to Target	12:1
Emissivity	0.1 to 1.00 (adjustable)
Dimensions	6.8x3.8x1.8" (172x97x46mm)
Weight	8oz (226g)

Ordering

IR260 ..... Compact InfraRed Thermometer

UPC Code: 793950422618

Specifications subject to change without notice. Copyright © 2015 FLIR Systems, Inc. All rights reserved including the right of reproduction in whole or in part in any form.
Rev. 12/8/15