

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0764953807

Status:

Active

Overview:

Impact™ Backplane Connector and Cable Assembly System

Description:

Impact™ 85 Ohm Plus 4 Pair, RAM Signal Module, Left Guided, 8 Columns, 96 Circuits, Plated Through Hole Dimension 0.39mm, Pin Length 4.90mm, Lead Free

Documents:

Drawing (PDF)

Product Specification PS-170540-999 (PDF)

Application Specification AS-76060-990 (PDF)

Packaging Specification PK-70873-041 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL

E29179

General

Product Family

Series

Application

Application Tooling Documents

Component Type

Overview

Product Name

UPC

Backplane Connectors

76495

Coplanar

TM-622018799

PCB Header

Impact™ Backplane Connector and Cable Assembly System

Impact™

887191541204

Physical

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

First Mate / Last Break

Flammability

Guide to Mating Part

Keying to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Net Weight

Number of Columns

Number of Pairs

Number of Rows

Orientation

PC Tail Length

PCB Locator

PCB Retention

PCB Thickness - Recommended

Packaging Type

Pitch - Mating Interface

Pitch - Termination Interface

Plating min - Mating

Polarized to PCB

Stackable

Surface Mount Compatible (SMC)

Temperature Range - Operating

Termination Interface: Style

96

96

Gray

200

No

94V-0

Yes

None

High Performance Alloy (HPA)

Gold

Tin

High Temperature Thermoplastic

17.359/g

8

4

12

Right Angle

1.20mm

No

None

1.00mm

Tray

1.35mm, 1.90mm

1.35mm, 1.90mm

0.762µm


No

No

No

-55°C to +85°C

Through Hole - Compliant Pin



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per
-ED/79/2015 (17
December 2015)

Halogen-Free

Status

Low-Halogen

Need more information on product
environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any
non-product compliance questions.

China ROHS
ELV

Green Image
Not Relevant

Search Parts in this Series

76495 Series

Mates With

170340 Impact™ 85 Ohm Plus 4 Pair, Right
Angle Daughtercard

Electrical

Current - Maximum per Contact	0.75A
Data Rate	25.0 Gbps
Impedance	85#
Shield Type	N/A
Shielded	No
Voltage - Maximum	30V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability	N/A
-----------------------------	-----

Material Info

Reference - Drawing Numbers

Application Specification	AS-76060-990
Electrical Model Document	EE-76495-0002
Packaging Specification	PK-70873-041
Product Specification	PS-170540-999
S-Parameter Model	SP-76495-0002
Sales Drawing	SD-76495-002
Symbol/Footprint Data	SYM-76495-3807

This document was generated on 06/10/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION