9050JCK70V20





Main

Range of product	9050JCK
Product or component type	Timer
Time delay type	Off-delay On-delay Interval One shot Repeat cycle On-delay and off-delay One shot falling edge Watchdog Trigger on-delay
Time delay range	0.059.99 s 0.199.9 s 1999 h 1999 min 1999 s 0.199.9 h
[Uc] control circuit voltage	120 V AC

Complementary

Hold-in power consumption in VA	3 VA	
Line Rated Current	10 A	_
Switch function	DPDT	
Contacts type and composition	2 NO + 2 NC	
Contacts material	Silver nickel	
Maximum switching voltage	240 V AC	
Mounting support	Socket	
Pin number	11	_
Shape of pin	Tubular	
Product compatibility	8501NR61 8501NR62	

Environment

		,
product certifications	CE RoHS UL listed UL recognized	
ambient air temperature for operation	-18150 °F	
height	2.36 in (60 mm)	
width	1.73 in (44 mm)	
depth	3.58 in (91 mm)	

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0703 - Schneider Electric declaration of conformity	Compliant - since 0703 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:

Nickel compounds, which is known to the State of California to cause cancer, and

Nickel compounds, which is known to the State of California to cause cancer, and

Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period 18 months

