


1. SCOPE

This specification covers the characteristics of the "SM" series size 2225, BX dielectric, 3.3 uF capacitance, +/- 10% tolerance, 50 VDC rated ceramic chip capacitors with surface mount "J" shaped leads.

2. DIELECTRIC CHARACTERISTICS - X7R

Operating Temperature Range:	-55°C to +125°C
Temperature Coefficient:	+/- 15% Change in capacitance @ 1 Vrms
Temperature Voltage Coefficient:	+15% -25% Change in capacitance @ 1 Vrms
Dissipation Factor:	2.5% Max. @ 25°C
Insulation Resistance, 25°C:	100 Giga-Ohms or 1000 Ohm-Farads, whichever is less
Insulation Resistance, 125°C:	10 Giga-Ohms or 100 Ohm-Farads, whichever is less
Dielectric Withstanding Voltage:	125 VDC
Aging Rate:	< 2.0% per decade
Test Parameters:	1KHz, 1.0 Volts +/- 0.2 Vrms, 25°C

3. PHYSICAL DIMENSIONS (NOT SCALED)



dimensions	E	D	X	C	Number of Leads per Side	n= Number of Units Stacked
inches (mm)	.300 (7.62)	.250 (6.35)	.440 (11.2)	.250 (6.35)	3	3
+/- in (mm)	Max	.025 (.635)	Max	.025 (.635)	n/a	n/a

4. PART NUMBER DESCRIPTION

SM 2225 X 335 K 500 LJ X H - 3

SM	= Stacked Capacitor Assembly (High Reliability Testing per Group A of Mil-Prf-49470)
2225	= Size
X	= BX Dielectric
335	= Capacitance Code (pF): First two digits are significant, third digit denotes number of zeros
K	= Capacitance tolerance: K = +/- 10%
500	= DC Voltage Rating: First two digits are significant, third digit denotes number of zeros
LJ	= Surface Mount Leads, "J" Shape
X	= Overall Height: .440" Max. (11.2mm Max.)
H	= High Reliability Testing
- 3	= Quantity of capacitors stacked in the assembly

REVISION: A

NOVACAP P/N: SM2225X335K500LJXH-3
CUSTOMER:
CUST. P/N:

SPEC DESIGNER MK 2/26/2016
SPEC MANAGER BN 2/26/2016
ENGINEERING BN 2/26/2016