



RoHS Compliant

REV	DESCRIPTION	DATE
A0	INITIAL RELEASE	2016-12-29



PIN ASSIGNMENTS

NOTES:

- 1.ELECTRICALTTEST:100%OPEN, SHORT&MIS WIRE TEST.
- 2.CONTACT RESISTANCE:10 ohm,
- 3.INSULATOR RESISTANCE:5M ohm.
- 4.HIGH VOLTAGE:DC 300V 0.01sec.
- 5.MUST BE ROHS COMPLIANT.

P1	COLOR	P2	P3
1	YELLOW	1	
2	BLUE	2	
3	ORANGE	3	
4	BROWN	4	
5	RED	5	
6	WHITE	6	
7	GREEN	7	
8	BLACK	8	28AWG BLACK 3
		9	28AWG RED 2
		10	28AWG WHITE 1

14	WIRE	UL1571 28AWG(7/0.12TC)OD:0.9mm RED/BLACK/WHITE	3 PCS
13	TUBE	OD1.5*10mm Black Heat Shrink TUBE	1 PCS
12	TUBE	OD8.0*15mm Black Heat Shrink TUBE	1 PCS
11	MOLDING	PVC 45P BLACK	11.5G
10	MOLDING	PE	6.50G
9	TIN WIRE	TIN WIRE OD:0.8MM	10.5G
8	SCREW	M3 OD3.0*Length 14mm SCREW	2 PCS
7	TIE	CABLE TIES COLOR:WHITE	1 PCS
6	TERMINAL	JST :SSH-003T-P0.2-H	10 PCS
5	HOUSING	JST:SHR-10V-S-B HOUSING:WHITE	1 PCS
4	TERMINAL	DUPONT:2.54 GOLD-PLATING	9 PCS
3	HOUSING	DUPONR:2.54-1*3P HOUSING:BLACK KEY10	1 PCS
2	CONNECTOR	双层USB A/F*2 PIN GOLD PLATED SHELL NICKEL PLASTIC:WHITE	1 PCS
1	CABLE	(12/0.11BC)*8C+AC+B(64/0.09TC) OD:5.2mm	1 PCS
序号	材料名称	规格描述	用量

图号 (DWG NO)		单位(UNIT) MM	品名 (ITEM NO) USB A/F TO JST PH1.0 10P HSG 料号 (PART NO)	
版次 (REV)	A0	比例(SCALE)任意		
页次 (PAGE)	1/1			
设计 (DESIGN)		未注公差 TOLERANCE UNSPECIFIED X.X ±0.25 X.XX ±0.15 X.XXX ±0.05 X" ±5" X.X" ±2"		
审核 (CHECKED)				
核准 (APPROVED)				