

4805 (3/11)

THIS DRAWING IS A C

		2					1					
	loc A D	D I S T		REVISIONS								
			Р	LTR		DESCRIPTION		DATE	DWN	APVD		
				D	REVISED PER	ECO-13-002771		22FEB2013	КН	RP		

CONTACT AND SHIELD - PHOS BRONZE HOUSING AND CHICKLET - LCP, UL 94V-0, COLOR - BLACK

CONTACT AREA FINISH CONFORMS TO THE REQUIREMENTS OF TE PRODUCT SPECIFICATION 108-2303; BASED ON

TELCORDIA GR-1217-CORE FOR SYSTEM QUALITY LEVEL III, APPLICATIONS IN CONTROLLED

ENVIRONMENTS (CENTRAL OFFICE). COMPLIANT PIN AREA- 0.5µm MIN MATTE TIN OVER 1.27µm MIN NICKEL. SHIELD I.27µm MIN NICKEL.

3 CONNECTOR MARKED ON EITHER SIDE OF HOUSING WITH PART NUMBER, DATE CODE AND STANDARD IN APPROXIMATE AREA SHOWN.

4 dimension applies to centerline of thru hole.

5 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.

6. CONTACT AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT. TECHNICAL REFERENCE: GR-1217-CORE, ISSUE I, NOVEMBER 1995.

 $\overline{27}$ reference application spec 114-13202 for recommended plated THRU HOLE DIAMETER AND PLATING THICKNESSES.

A THE GROUNDS IN EACH COLUMN ARE COMMONED.

|93422|-PART NUMBER

CONTROLLED DOCUMENT.	DWN 3 I JAN 2007 S. J. MAGARO снк 3 I JAN 2007 W. DAV I S	TE Connectivity					
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 3 PLC +-	APVD 27AUG2007 R.PATTERSON PRODUCT SPEC - APPLICATION SPEC	RECEPTACLE ASSEMBLY, 5 PAIR, 16 COLUMN -					
4 PLC ±- ANGLES ±-	-	SIZE CAGE CODE DRAWING NO		RESTRICTED TO			
FINISH -	WEIGHT _	$A 00779 \mathbb{C} - 19$	34221	-			
- / 2	CUSTOMER DRAWING		SCALE G. SHEET (