

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1552210001](#)  
**Status:** **Active**  
**Overview:** [Flamar Standard Cables for Industrial Automation](#)  
**Description:** Flamar Sensor Cable, WSOR Jacket, Braided Shielding Overall, 3 Circuits, 22 AWG, 5.40mm Diameter, 600.0m Length, Black

**Documents:**

[RoHS Certificate of Compliance \(PDF\)](#)

[Product Literature \(PDF\)](#)

**General**

Product Family	Cable
Series	<a href="#">155221</a>
Bending Radius - Minimum	> 7.5xOD
Color - Cable Jacket	Black
Comments	3 reels of 200.0m each
Crimp Quality Equipment	Yes
Geographic Area	Global
Material - Outer Jacket	WSOR
Outer Jacket Diameter	5.40mm (.213")
Overview	<a href="#">Flamar Standard Cables for Industrial Automation</a>
Product Literature Order No	987651-3992
Product Name	Flamar
UPC	889056463638

**Physical**


Cable Length	600.0m
Circuits (Loaded)	3
Insulation	TPE
Net Weight	0.010/g
Packaging Type	Reel
Temperature Range - Operating	-25°C to +80°C
Wire Size AWG	22
Wire Size mm <sup>2</sup>	0.34
Wire/Cable Type	Signal and Control, UL AWM 21215 / CSA

**Electrical**

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V

**Material Info**

Old Part Number	BS1-3-3X200M
-----------------	--------------



*Series image - Reference only*

**EU ELV**

**Not Reviewed**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Not Reviewed

ELV

Not Reviewed

**Search Parts in this Series**

[155221](#) Series

**Use With**

Nano-Change® (M8) [120091](#) , Micro-Change® (M12) [120071](#) , Ultra-Lock® (M12) [120085](#)