



- NOTES
- 1 One example of the rotation of Ref. No. ⑤ to Ref. No. ① is shown.
 - 2 The recommended torque of Ref. No. ⑤ : 2 TO 3 N·m.
 - 3 Across flats hexagon head of Ref. No. :1.27 the recommended clamp torque of Ref. No. ⑧ : 0.3 to 0.4 N·m.
 - 4 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure. Please confirm before the use.
 - 5 LOCTITE 243 HENKEL JAPAN or equivalent is recommended to prevent Ref. No. ①, ⑦ and ⑧ for loosening.

4	DIALYL PHTHALATE	(BLACK)	UL94V-0	8	STEEL	NICKEL PLATING	HEXAGON SOCKET SET SCREW M2. 6X0. 45X2
3	DIALYL PHTHALATE	(BLACK)	UL94V-0	7	BRASS	NICKEL PLATING	JIS B 1101 M2X0. 4X8
2	COPPER ALLOY	SILVER PLATING	2 μm min.	6	ZINC ALLOY	MATTE FINISH NICKEL PLATED	
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED		5	ZINC ALLOY	MATTE FINISH NICKEL PLATED	
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED
HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI	15. 10. 27	DRAWING NO.	EDC-027939-00-00	
		CHECKED	HY. KOBAYASHI	15. 10. 27	PART NO.	RM12BJB-7PH	
		DESIGNED	HT. ZENBA	15. 10. 26	CODE NO.	CL109-0834-4-00	
		DRAWN	HT. ZENBA	15. 10. 26			1/1