

For more Information
please call

1-800-Belden1



Description:

Tinned copper conductor, PVC insulation.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	8	133x29	TC - Tinned Copper

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.045

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.262 in.

Mechanical Characteristics (Overall)

Bulk Cable Weight: 74 lbs/1000 ft.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating:	600 V, 105°C
UL Type:	MTW or TW or AWM 1015/1028/1231
CSA Rating:	600 V, 105°C
CSA Type:	TEW or AWM I A/B
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test: VW-1

Plenum/Non-Plenum

Plenum (Y/N): No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

8908 Hook-up/Lead - UL AWM Style 1028 and 1015

8908 001250	250 FT	19.750 LB	BROWN		#8 STR PVC BRN
8908 002250	250 FT	18.250 LB	RED		#8 STR PVC RED
8908 0041500	1,500 FT	114.000 LB	YELLOW		#8 STR PVC YEL
8908 004250	250 FT	19.750 LB	YELLOW		#8 STR PVC YEL
8908 005250	250 FT	19.750 LB	GREEN, DARK	C	#8 STR PVC DGRN
8908 0071500	1,500 FT	114.000 LB	VIOLET		#8 STR PVC VIO
8908 0081500	1,500 FT	114.000 LB	GRAY		#8 STR PVC GRY
8908 008250	250 FT	19.750 LB	GRAY		#8 STR PVC GRY
8908 0101500	1,500 FT	114.000 LB	BLACK		#8 STR PVC BLK
8908 010250	250 FT	18.250 LB	BLACK	C	#8 STR PVC BLK
8908 013250	250 FT	19.750 LB	BLUE, DARK		#8 STR PVC DBLU

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 06-03-2011

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.