

RTV Silicones



RTV Silicones by **2-Part Potting/Encapsulating Compound**
RTV88



Technical Support
for RTV Silicones

1-800-255-8886

ALL MG PRODUCTS ▾

▶ STOCKED ITEM

▶ BUY NOW

Jump to Product Number



- [Accessories](#)
- [Adhesives](#)
- [Brushes](#)
- [Cleaners / Degreasers](#)
- [Contact Cleaners](#)
- [Desoldering Braid](#)
- [Dusters & Circuit Coolers](#)
- [EMI / RFI Shielding](#)
- [Epoxyes](#)
- [Flux and Flux Remover](#)
- [Glass & Screen Cleaners](#)
- [Isopropyl Alcohol](#)
- [Lead Free Solder](#)
- [Lubricants](#)
- [Potting & Encapsulating](#)
- [Protective Coatings](#)
- [Pens](#)
- [Prototyping Materials](#)
- [RTV Silicones](#)
- [Soldering/desoldering](#)
- [Specialized Cleaners](#)
- [Swabs](#)
- [Thermal Management](#)
- [Thermally Conductive Adhesives](#)
- [Wipes](#)

Primary Characteristics

- ▶ **Red spreadable**
- ▶ **Condensation cure**
- ▶ **Extreme high temp**
- ▶ **Useful to 260°C (500°F)**
- ▶ **Primer required**

Use for:

▶ Aerospace applications such as potting, encapsulating, coating and cushioning

Excellent for potting and encapsulating electric motors, transformers, and surge protection. Can be used in aerospace applications such as sealing, bonding and quaking on vertical or overhead surfaces. Composition is free of solvents and solvent odour. Excellent retention of elastomeric properties at temperatures from -54°C to 260°C (-65°F to 500°F) continuously, and up to 316°C (600°F) for short periods of time. This two part silicone is supplied with a curing agent. Silicone [primer](#) is required. Cures at room temperature and has excellent adhesion qualities. The product comes complete with catalyst DBT. [Specialized catalysts](#) are available upon request.

Available Sizes

Catalog Number	Sizes Available	Description
RTV88-1P	1 pint	pail
RTV88-1G	1 gallon	pail
RTV88-5G	5 gallon	pail
RTV88 requires a primer. Visit our primer guide for details.		

Specifications

Use	Potting & Encapsulating
Special Feature	High Temperature
Cross Reference	RTV80
Uncured Properties	
Consistency	Spreadable
Color	Red
Specific Gravity	1.47
Pot Life	45 minutes
Cure Through Time	24 hours
Useful Temp. Range	-54°C to 260°C (-65°F to 500°F)
Cured Properties - MECHANICAL	
Hardness	58 (Shore A)
Tensile Strength	5.79 MPa (830 psi)

M.G. Chemicals Disclaimer
for RTV Silicones >

[Locate Distributor >](#)

Quick Links

- ▶ [MSDS](#)
- ▶ [Catalyst options/MSDS](#)
- ▶ [Primer options/MSDS](#)
- ▶ [Specifications](#)
- ▶ [Available Sizes](#)

Related products:

- [RTV21](#)
- [RTV31](#)
- [RTV60](#)
- [RTV88](#)
- [RTV560](#)
- [RTV566](#)
- [RTV577](#)
- [RTV630](#)
- [RTV656](#)

Resources

- ▶ [Selection Guide >](#)
- ▶ [One Part Chart](#)
- ▶ [Two Part Chart](#)

Find by Application

- [General Purpose >](#)
- [Aerospace >](#)
- [Marine >](#)
- [High Performance Assembly >](#)
- [Electronics >](#)
- [Thermal Conductivity >](#)
- [High Temperature >](#)
- [Low Temperature >](#)



Elongation	120%
Cured Properties - ELECTRICAL	
Volume Resistivity	2.8×10^{14} ohm · cm
Dielectric Strength	17.4 kV/mm (440 V/mil)
Dielectric Constant	4.3 @ 1000Hz
Cured Properties - THERMAL	
Thermal Conductivity	0.31 W/m · °K
Thermal Expansion	20×10^{-5} cm/cm °C (11×10^{-5} in/in °F)
Other	
Viscosity (@ 25°C)	880,000 cps
Mix ratio (by weight)	100:0.5

[Return to top](#) ^