




100 V power Schottky rectifier



Features

- Low profile design package height of 1.1 mm typ.
- · Wettable flanks for automatic visual inspection
- · Low forward voltage drop
- Avalanche capability
- ECOPACK®2 compliant

Applications

- · Switching diode
- Notebook adapter
- LED lighting
- DC/DC converter

Description

This high voltage Schottky barrier rectifier has been optimized for use in high frequency miniature DC/DC converters, reverse battery protection, battery chargers and adaptors.

Packaged in PSMC (TO-277A), the STPS5H100SF provides a high level of performance in a compact and flat package which can withstand very high operating junction temperature.

Product status link				
STPS5H100SF				
Product summary				
Symbol	Symbol Value			
I _{F(AV)}	5 A			
V _{RRM}	100 V			
T _j (max.)	175 °C			
V _F (typ.)	0.545 V			



1 Characteristics

Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified, anode terminals short-circuited)

Symbol	Parameter	Value	Unit	
V _{RRM}	Repetitive peak reverse voltage	100	V	
I _{F(AV)}	Average forward current, δ = 0.5 square wave	T _c = 160 °C	5	Α
I _{FSM}	Surge non repetitive forward current $t_p = 10 \text{ ms sinusoidal}$		230	Α
P _{ARM}	Repetitive peak avalanche power	518	W	
T _{stg}	Storage temperature range	-65 to +175	°C	
T _j	Maximum operating junction temperature ⁽¹⁾ +175			

^{1.} $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$ condition to avoid thermal runaway for a diode on its own heatsink.

Table 2. Thermal resistance parameters

Symbol	Parameter	Тур.	Unit
$R_{th(j-c)}$	Junction to case	2.1	°C/W

For more information, please refer to the following application note:

AN5088: Rectifiers thermal management, handling and mounting recommendations

Table 3. Static electrical characteristics (anode terminals short-circuited)

Symbol	Parameter	Test conditions		Min.	Тур.	Max.	Unit
I_ (1)	I _R ⁽¹⁾ Reverse leakage current	T _j = 25 °C	\ \ -\\	-		8	μA
'R'		T _j = 125 °C	$V_R = V_{RRM}$	-	1.5	5	mA
	Forward voltage drop	T _j = 25 °C	I _F = 2.5 A	-		0.640	V
V _F ⁽²⁾		T _j = 125 °C		-	0.480	0.540	
VF(=)		T _j = 25 °C	I _F = 5 A	-		0.745	
		T _j = 125 °C		-	0.545	0.610	

- 1. Pulse test: t_p = 5 ms, δ < 2%
- 2. Pulse test: t_p = 380 μ s, δ < 2%

To evaluate the conduction losses, use the following equation:

 $P = 0.470 \times I_{F(AV)} + 0.028 \times I_{F^{2}(RMS)}$

For more information, please refer to the following application notes related to the power losses:

- AN604: Calculation of conduction losses in a power rectifier
- AN4021: Calculation of reverse losses in a power diode

DS12694 - Rev 1 page 2/9



1.1 **Characteristics (curves)**





Figure 2. Relative variation of thermal impedance junction to case versus pulse duration $Z_{th(j\text{-}c)}/R_{th(j\text{-}c)}$ 1.0 0.9 0.8 0.7 0.6 0.5 0.4 0.3 0.2 0.1 tp(s) 0.0 1.E-03 1.E-02 1.E-01 1.E+00 1.E-04

applied (typical values) $I_R(\mu A)$ 1.E+04 1.E+03 1.E+02 1.E+01 1.E+00 1.E-01 $V_R(V)$ 1.E-02 90 10 50



DS12694 - Rev 1 page 3/9



Figure 5. Forward voltage drop versus forward current (typical values) 10.0 T_j = 75 °C $V_F(V)$ 0.1 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 8.0 0.9

Figure 6. Normalized avalanche power derating versus pulse duration (T_j = 125 °C)


PARM(tp)
PARM(10 µs)

0.01

0.01

1 10 100 1000

Figure 7. Thermal resistance junction to ambient versus copper surface under tab (typical values, epoxy printed board FR4, e_{Cu} = 35 μ m) (PSMC (TO-277A))



DS12694 - Rev 1 page 4/9



2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK[®] packages, depending on their level of environmental compliance. ECOPACK[®] specifications, grade definitions and product status are available at: www.st.com. ECOPACK[®] is an ST trademark.

2.1 PSMC (TO-277A) package information

- Epoxy meets UL94,V0
- Cooling method : by conduction (C)




Figure 8. PSMC (TO-277A) package outline

Table 4. PSMC (TO-277A) package mechanical data


	Dimensions					
Ref.		Millimeters		Inch	nes (for reference o	nly)
	Min.	Тур.	Max.	Min.	Тур.	Max.
Α	1.00	1.10	1.20	0.039	0.043	0.047
b	1.05	1.20	1.35	0.041	0.047	0.053
b2	1.90	2.05	2.20	0.075	0.081	0.087
b4		0.75			0.029	
С	0.15	0.23	0.40	0.006	0.009	0.016
D	4.45	4.60	4.75	0.175	0.181	0.187
D1	4.25	4.40	4.45	0.167	0.173	0.175
D2	3.40	3.60	3.70	0.134	0.142	0.146

DS12694 - Rev 1 page 5/9



		Dimensions						
Ref.		Millimeters			Inches (for reference only)			
	Min.	Тур.	Max.	Min.	Тур.	Max.		
E	6.35	6.50	6.65	0.250	0.256	0.262		
E1	6.05	6.10	6.15	0.238	0.240	0.242		
E2	4.50	4.60	4.70	0.177	0.181	0.185		
E3		3.94			1.55			
е		2.13			0.084			
e1		3.33			0.131			
G		1.20			0.047			
G1		0.70			0.027			
L	0.90	1.05	1.24	0.035	0.041	0.049		
L4	0.02			0.0008				
L5	0.02			0.0008				

Figure 9. PSMC (TO-277A) package footprint in mm (in inches)



DS12694 - Rev 1 page 6/9



3 Ordering information

Table 5. Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
STPS5H100SF	PS5H100	PSMC (TO-277A)	90 mg	6000	Tape and Reel

DS12694 - Rev 1 page 7/9



Revision history

Table 6. Document revision history

Date	Version	Changes
30-Jul-2018	1	Initial release.

DS12694 - Rev 1 page 8/9



IMPORTANT NOTICE - PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics - All rights reserved

DS12694 - Rev 1 page 9/9