

## 6A, 200V - 600V Surface Mount Ultrafast Rectifiers

### FEATURES

- Very low profile, typical height of 1.1mm
- Excellent high temperature stability
- Glass passivated chip junction
- Controlled avalanche characteristics
- Low leakage current
- High forward surge capability
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

### TYPICAL APPLICATIONS

For use in high voltage, high frequency power factor corrections, switching mode power supplies, freewheeling diodes and secondary dc to dc rectifications

### MECHANICAL DATA

**Case:** TO-277A (SMPC)

Molding compound, UL flammability classification rating 94V-0

Moisture sensitivity level: level 1, per J-STD-020

Part no. with suffix "H" means AEC-Q101 qualified


Packing code suffix "G" means green compound (halogen-free)

**Terminal:** Matte tin plated leads, solderable per JESD22-B102


Meet JESD 201 class 1A whisker test

**Polarity:** Indicated by cathode band

**Weight:** 95 mg (approximately)



TO-277A (SMPC)



| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted) |     |                                                                  |                                 |                 |                      |        |      |      |   |
|----------------------------------------------------------------------------------------------|-----|------------------------------------------------------------------|---------------------------------|-----------------|----------------------|--------|------|------|---|
| PARAMETER                                                                                    |     |                                                                  | SYMBOL                          | TPUH6D          |                      | TPUH6J |      | UNIT |   |
| Marking code                                                                                 |     |                                                                  |                                 | UH6D            |                      | UH6J   |      |      |   |
| Maximum repetitive peak reverse voltage                                                      |     |                                                                  | V <sub>RRM</sub>                | 200             |                      | 600    |      | V    |   |
| Maximum average forward rectified current                                                    |     |                                                                  | I <sub>F(AV)</sub>              | 6               |                      |        |      | A    |   |
| Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load          |     |                                                                  | I <sub>FSM</sub>                | 80              |                      |        |      | A    |   |
| Maximum instantaneous forward voltage <sup>(1)</sup>                                         |     | Test condition                                                   |                                 | V <sub>F</sub>  | TYP                  | MAX    | TYP  | MAX  | V |
|                                                                                              |     | I <sub>F</sub> =3A                                               | T <sub>J</sub> =25°C            |                 | 0.80                 | -      | 1.98 | -    |   |
|                                                                                              |     |                                                                  | T <sub>J</sub> =125°C           |                 | 0.65                 | -      | 1.23 | -    |   |
|                                                                                              |     | I <sub>F</sub> =6A                                               | T <sub>J</sub> =25°C            |                 | 0.87                 | 1.05   | 2.45 | 3.00 |   |
|                                                                                              |     |                                                                  | T <sub>J</sub> =125°C           |                 | 0.73                 | 0.90   | 1.59 | 1.80 |   |
|                                                                                              |     | Maximum reverse current @ rated V <sub>R</sub>                   |                                 |                 | T <sub>J</sub> =25°C | 10     |      |      |   |
| T <sub>J</sub> =125°C                                                                        | 200 |                                                                  |                                 |                 |                      |        |      |      |   |
| Maximum reverse recovery time                                                                |     | I <sub>F</sub> =0.5A, I <sub>R</sub> =1A, I <sub>RR</sub> =0.25A |                                 | t <sub>rr</sub> | 25                   |        |      | ns   |   |
|                                                                                              |     | I <sub>F</sub> =1A, di/dt=-50A/μs, V <sub>R</sub> =30V           |                                 |                 | 45                   |        |      |      |   |
| Typical thermal resistance                                                                   |     |                                                                  | R <sub>θJM</sub> <sup>(2)</sup> | 12              |                      |        |      | °C/W |   |
|                                                                                              |     |                                                                  | R <sub>θJA</sub> <sup>(3)</sup> | 80              |                      |        |      |      |   |
| Typical junction capacitance <sup>(4)</sup>                                                  |     |                                                                  | C <sub>J</sub>                  | 50              |                      |        |      | pF   |   |
| Operating junction temperature range                                                         |     |                                                                  | T <sub>J</sub>                  | - 55 to +175    |                      |        |      | °C   |   |
| Storage temperature range                                                                    |     |                                                                  | T <sub>STG</sub>                | - 55 to +175    |                      |        |      | °C   |   |

Note 1: Pulse test with PW=300μs, 1% duty cycle

Note 2: Mounted on FR4 PCB with 16mm x 16mm Cu pad area

Note 3: Free air, mounted on recommended pad

Note 4: Measured at 1 MHz and Applied V<sub>R</sub>=4.0 V

| ORDERING INFORMATION  |                 |              |                     |         |                         |
|-----------------------|-----------------|--------------|---------------------|---------|-------------------------|
| PART NO.              | PART NO. SUFFIX | PACKING CODE | PACKING CODE SUFFIX | PACKAGE | PACKING                 |
| TPUH6x<br>(Note 1, 2) | H               | S1           | G                   | SMPC    | 1,500/ 7" Plastic reel  |
|                       |                 | S2           |                     | SMPC    | 6,000/ 13" Plastic reel |

Note 1: "x" defines voltage from 200V (TPUH6D) to 600V (TPUH6J)

Note 2: Whole series with green compound

| EXAMPLE            |          |                 |              |                     |                                      |
|--------------------|----------|-----------------|--------------|---------------------|--------------------------------------|
| PREFERRED PART NO. | PART NO. | PART NO. SUFFIX | PACKING CODE | PACKING CODE SUFFIX | DESCRIPTION                          |
| TPUH6JHS1G         | TPUH6J   | H               | S1           | G                   | AEC-Q101 qualified<br>Green compound |

## RATINGS AND CHARACTERISTICS CURVES

( $T_A=25^{\circ}\text{C}$  unless otherwise noted)

FIG. 1 MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPETITIVE FORWARD PEAK SURGE CURRENT




FIG. 4 TYPICAL REVERSE CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE






FIG.6 REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




PACKAGE OUTLINE DIMENSIONS  
TO-277A (SMPC)



| DIM. | Unit (mm) |       | Unit (inch) |       |
|------|-----------|-------|-------------|-------|
|      | Min       | Max   | Min         | Max   |
| A    | 5.650     | 5.750 | 0.222       | 0.226 |
| B    | 6.350     | 6.650 | 0.250       | 0.262 |
| C    | 4.550     | 4.650 | 0.179       | 0.183 |
| D    | 3.540     | 3.840 | 0.139       | 0.151 |
| E    | 4.235     | 4.535 | 0.167       | 0.179 |
| F    | 1.850     | 2.150 | 0.073       | 0.085 |
| G    | 3.170     | 3.470 | 0.125       | 0.137 |
| H    | 1.043     | 1.343 | 0.041       | 0.053 |
| I    | 1.000     | 1.300 | 0.039       | 0.051 |
| J    | 1.930     | 2.230 | 0.076       | 0.088 |
| K    | 0.175     | 0.325 | 0.007       | 0.013 |
| L    | 1.000     | 1.200 | 0.039       | 0.047 |

SUGGESTED PAD LAYOUT



| Symbol | Unit (mm) | Unit (inch) |
|--------|-----------|-------------|
| A      | 4.80      | 0.189       |
| B      | 4.72      | 0.186       |
| C      | 1.40      | 0.055       |
| D      | 1.27      | 0.050       |
| E      | 6.80      | 0.268       |
| F      | 1.04      | 0.041       |

MARKING DIAGRAM



P/N = Marking Code  
YW = Date Code  
F = Factory Code

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.