

# SPECIFICATION CONTROL DRAWING

**55/4322**

TITLE


TWO CONDUCTOR CABLE, JACKETED, OUTER SPACE, 600 VOLT

Date 3-21-12

Revision C

This specification sheet forms a part of the latest issue of Raychem Specification 55/.

COMPONENT WIRES - 55/0312

JACKET - LOW OUTGASSING,  
RADIATION-CROSSLINKED,  
MODIFIED ETFE

## CABLE CONSTRUCTION DETAILS

| PART NUMBER<br><u>1/</u> | CONDUCTOR<br>SIZE<br>(AWG) | JACKET THICKNESS<br>(in.) |         | OUTSIDE DIAMETER<br>(in.) |         | MAXIMUM<br>WEIGHT<br>(lbs/1000 ft.) |
|--------------------------|----------------------------|---------------------------|---------|---------------------------|---------|-------------------------------------|
|                          |                            | MINIMUM                   | NOMINAL | NOMINAL                   | MAXIMUM |                                     |
| 55/4322-26-*             | 26                         | .0040                     | .0050   | .064                      | .067    | 3.15                                |
| 55/4322-24-*             | 24                         | .0040                     | .0050   | .074                      | .078    | 4.42                                |
| 55/4322-22-*             | 22                         | .0040                     | .0050   | .088                      | .092    | 6.39                                |
| 55/4322-20-*             | 20                         | .0040                     | .0050   | .109                      | .113    | 9.79                                |
| 55/4322-18-*             | 18                         | .0045                     | .0055   | .129                      | .133    | 14.65                               |
| 55/4322-16-*             | 16                         | .0045                     | .0055   | .144                      | .148    | 18.42                               |
| 55/4322-14-*             | 14                         | .0050                     | .0060   | .174                      | .179    | 27.94                               |
| 55/4322-12-*             | 12                         | .0050                     | .0060   | .212                      | .218    | 42.40                               |
| 55/4322-10-*             | 10                         | .0060                     | .0070   | .266                      | .275    | 67.55                               |

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

### TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

CROSSLINKED VERIFICATION: 300 ± 3°C for 1 hour

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz

JACKET COLOR: White preferred

JACKET ELONGATION: 50% (minimum)

RADIATION RESISTANCE: 500 megarads

### VACUUM STABILITY:

Total Mass Loss (TML), 1.00% (maximum)

Volatile Condensable Material (VCM), 0.10% (maximum)

### PART NUMBER:

The "\*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.

1/ Example: AWG 22, black and brown component wires;  
white jacket: 55/4322-22-0/1-9

NOTE: Nominal values are for information only.

Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.

Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

Raychem, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.  
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.



Raychem Wire & Cable  
501 Oakside Avenue  
Redwood City, CA 94063-3800  
Phone: 1-800-227-8816  
Fax: 1-650-361-6297