


CIRCUIT DIAGRAM

SWITCH FUNCTION

TERM. #	FUNCTION
2-1, 5-4	NORM. CLOSED POS. 1
2-3, 5-6	NORM. OPEN POS.2
2, 5	COMMON

NOTE:

1. ALL DIMENSIONS IN mm [INCH]
2. GENERAL TOLERANCE: $x.x \pm 0.4$
 $x.xx \pm 0.25$
3. TERMINAL NUMBERS FOR REF. ONLY
4. CONTACT RATING: 0.1A @ 30 VDC
- ▲ 5. TRAVEL: FULL= 1.8mm; LOCKING= 1.0mm
- ▲ 6. OPERATING FORCE: 100± 50gf
7. ELECTRICAL LIFE: 10,000 CYCLES
8. ▲ DENOTES CRITICAL PARAMETER
9. CONTACT MATERIAL: SILVER
10. 2002/95/EC (RoHS) COMPLIANT



B	19638	DRAWING UPDATE /	TERM. DIM .5 to .6	2/10/11	BGL
REV	PCR NO	DESCRIPTION		DATE	BY
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED					

TITLE TL2230EEF100				
SCALE 3:1	DATE 2/8/2011	DR BGL	DWG D310402	REV B