




1	2	3	4	5	6	7	8
REV.	ECN NO.	DATE	SIGN	DESCRIPTION			




⑤ Sealing Nut




④ Seals B2







③ Clamp Ring



② Seals B1



① Housing

With Liquid Glue
點防水膠Pin Assignments
Front View 前視圖

Note:

- * Seals B1 for Cable OD: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$
(防水墊圈B1線徑: $\varnothing 4.5\text{mm} \sim \varnothing 6.5\text{mm}$)
- * Seals B2 for Cable OD: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$
(防水墊圈B2線徑: $\varnothing 3.5\text{mm} \sim \varnothing 5.3\text{mm}$)
- * One Set Unassembled in One PE Bag
(每一組未組裝, 放置於一個PE袋, 並封口)
- * Important Dimension.
- * Waterproof Rate : IP66
- * Housing: Black, Nylon+GF
- * Pin: Copper Alloy, Gold Plated
- * Seals: Black, EPDM
- * Clamping Ring: Black, Nylon
- * Sealing Nut: Black, Nylon
- * PE Bag: 90mm*85mm
- * Liquid Glue: Clear

UNIT: mm				TITLE Standard, Assy Lock 7Pin M Conn M Pin		ITEM NO BD-07BMMA-LL6001	DRAWN BY SamChang	DATE 2012-03-27
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 1:1	SIZE A4	SHEET 1	OF 1	DWG NO BD-07BMMA-LL6001	CHECKED BY Jeffrey	DATE 2012-04-05
REV. A		WC-REV. A.2	Inspection item			CUSTOMER ALTW	APPROVED BY Lion	DATE 2012-04-05

Amphenol LTW
安費諾亮泰企業股份有限公司