


- NOTES:
- MATERIALS AND FINISHES:
BODY, CONTACT-OUTER - BRASS, NICKEL PLATING
CONTACT - BeCu, GOLD PLATING
CONTACT - BRASS, GOLD PLATING
INSULATORS - PTFE
FERRULE - COPPER, NICKEL PLATING
HEAT SHRINK TUBING - CROSSLINKED POLYOLEFIN
 - ELECTRICAL:
A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 6 GHz
C. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS, MIN.
 - MECHANICAL:
A. DURABILITY: 500 CYCLES MIN.
B. TEMPERATURE RANGE: -55° C TO +85° C
 - PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 82-6517, AND DATE CODE"

- 5> RECOMMENDED CABLE ASSEMBLY INSTRUCTIONS:
- TRIM CABLE AS SHOWN.
 - SLIDE HEAT SHRINK TUBING, FERRULE AND INSULATOR DISC ONTO CABLE.
 - SOLDER CABLE CENTER CONDUCTOR TO CONTACT.
 - INSERT CABLE WITH FOIL ENTERING CONNECTOR AND BRAID OVER KNURL.
 - CRIMP FERRULE OVER BRAID WITH 0.532" HEX DIE
 - APPLY HEAT SHRINK TUBING OVER FERRULE.
 - HEAT SHRINK TUBING SHOULD FULLY (360 DEG) COVER THE BUMP ON BODY AND END WITHIN AREA "A"

6> SHOWS CABLE ENTRY DIMENSIONS.



CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm ± 0.05mm 0.5 - 6mm ±0.1mm 6 - 30mm ±0.2mm 30 - 120mm ± 0.3mm ANGLES ±1°	MATERIAL	DRAWN T.DENG	DATE 16-Jul-12	TITLE N JACK STR IP-67 FOR LMR-400 CABLE		Amphenol RF www.amphenolrf.com	
		ENGINEER D.DAVE	DATE 15-Sep-11				
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	REFERENCE EAR # 3410	APPROVED D.HU	DATE 01-Aug-12	SCALE: 2.3:1.0 SHEET 2 OF 2		DRAWING NO.82-6517	
	CONFIGURATION LEVEL:	CAD FILE		DWG SIZE B		REV A	ITEM NO.82-6517
	FINISH						PART NO.82-6517