





Submersible EMI/RFI Cable Sealing Backshell with Strain Relief Type G - Direct Coupling - Low Profile



CONNECTOR DESIGNATORS A-B*-C-D-E-F G-H-J-K-L-S

* Conn. Desig. B See Note 5
DIRECT COUPLING


TYPE G INDIVIDUAL AND/OR OVERALL SHIELD TERMINATION



STYLE C Medium Duty (Table X)



STYLE E Medium Duty (Table XI)



Submersible EMI/RFI Cable Sealing Backshell with Strain Relief Type G - Direct Coupling - Low Profile



See inside back cover fold-out or pages 13 and 14 for Tables I and II.

TABLE III: FRONT ADAPTER			
Shell Size	J Max - Conn. Designator		
	A-E-F J-H-L-S	D-B-G-K	C
08/09	1.180 (30.0)	1.440 (36.6)	
10/11	1.180 (30.0)	1.440 (36.6)	
12/13	1.180 (30.0)	1.440 (36.6)	1.735 (44.1)
14/15	1.180 (30.0)	1.440 (36.6)	1.915 (48.6)
16/17	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
18/19	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
20/21	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
22/23	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
24/25	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
28/29	1.610 (40.9)	1.560 (39.6)	1.915 (48.6)
32/33	1.610 (40.9)	1.750 (44.5)	1.915 (48.6)
36	1.610 (40.9)	1.750 (44.5)	1.915 (48.6)
40	1.610 (40.9)	2.190 (55.6)	1.915 (48.6)

TABLE IV					
Dash No.	E Max	F Max	G Max	H Max	
03	.500 (12.7)	1.250 (31.8)	.520 (13.2)	1.140 (29.0)	
04	.500 (12.7)	1.610 (40.9)	.520 (13.2)	1.170 (29.7)	
06	.590 (15.0)	1.730 (43.9)	.580 (14.7)	1.650 (41.9)	
08	.610 (15.5)	1.750 (44.5)	.640 (16.3)	1.720 (43.7)	
10	.700 (17.8)	1.820 (46.2)	.730 (18.5)	1.800 (45.7)	
12	.880 (22.4)	2.080 (52.8)	.920 (23.4)	1.910 (48.5)	
16	.970 (24.6)	2.190 (55.6)	1.020 (25.9)	2.100 (53.3)	
20	1.120 (28.4)	2.190 (55.6)	1.040 (26.4)	2.250 (57.2)	
24	1.220 (31.0)	2.360 (59.9)	1.040 (26.4)	2.300 (58.4)	
28	1.570 (39.9)	2.610 (66.3)	1.090 (27.7)	2.400 (61.0)	
32	1.770 (45.0)	2.780 (70.6)	1.180 (30.0)	2.600 (66.0)	

TABLE X							
Dash No.	T Max	W Max	X Ref	Cable Range			
				Min		Max	
03	1.219 (31.0)	.812 (20.6)	.135 (3.4)	.156 (4.0)		.219 (5.6)	
04	1.219 (31.0)	.937 (23.8)	.203 (5.2)	.188 (4.8)		.312 (7.9)	
06	1.219 (31.0)	1.062 (27.0)	.285 (7.2)	.281 (7.1)		.438 (11.1)	
08	1.219 (31.0)	1.188 (30.2)	.350 (8.9)	.312 (7.9)		.531 (13.5)	
10	1.281 (32.5)	1.312 (33.3)	.390 (9.9)	.375 (9.5)		.625 (15.9)	
12	1.281 (32.5)	1.562 (39.7)	.460 (11.7)	.500 (12.7)		.750 (19.1)	
16	1.406 (35.7)	1.750 (44.5)	.510 (13.0)	.625 (15.9)		.938 (23.8)	
20	1.656 (42.1)	2.250 (57.2)	.695 (17.7)	.938 (23.8)		1.250 (31.8)	
24	1.906 (48.4)	2.375 (60.3)	.715 (18.2)	1.000 (25.4)		1.375 (34.9)	
28	1.906 (48.4)	2.625 (66.7)	.915 (23.2)	1.250 (31.8)		1.625 (41.3)	
32	2.000 (50.8)	2.812 (71.4)	1.070 (27.2)	1.500 (38.1)		1.875 (47.6)	

TABLE XI					
Dash No.	Y Max	Z Max	Cable Range		
			Min		Max
03	.739 (18.8)	.812 (20.6)	.156 (4.0)		.219 (5.6)
04	.739 (18.8)	.937 (23.8)	.188 (4.8)		.312 (7.9)
06	.739 (18.8)	1.062 (27.0)	.281 (7.1)		.438 (11.1)
08	.739 (18.8)	1.188 (30.2)	.312 (7.9)		.531 (13.5)
10	.791 (20.1)	1.312 (33.3)	.375 (9.5)		.625 (15.9)
12	.880 (22.4)	1.562 (39.7)	.500 (12.7)		.750 (19.1)
16	.901 (22.9)	1.750 (44.5)	.625 (15.9)		.938 (23.8)
20	1.031 (26.2)	2.250 (57.2)	.938 (23.8)		1.250 (31.8)
24	1.250 (31.8)	2.375 (60.3)	1.000 (25.4)		1.375 (34.9)
28	1.250 (31.8)	2.625 (66.7)	1.250 (31.8)		1.625 (41.3)
32	1.312 (33.3)	2.812 (71.4)	1.500 (38.1)		1.875 (47.6)

1. Metric dimensions (mm) are indicated in parentheses.
2. Cable range is defined as the accommodations range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.
3. Consult factory for shorter lengths on straight backshells.
4. Saddles are bottomed on Clamp Ears.
5. When using Connector Designator B refer to pages 18 and 19 for part number development.